



# MATERIAL SAFETY DATA SHEET

---

---

## Section 1: Product & Company Identification

---

---

**Product Name:** Nickel Anti-Seize and Lubricating Compound

**Product Number (s):** SL35911, SL35913

**Product Use:** general purpose anti-seize lubricant

### Manufacturer / Supplier Contact Information:

In United States:

CRC Industries, Inc.

885 Louis Drive

Warminster, PA 18974

[www.crcindustries.com](http://www.crcindustries.com)

1-215-674-4300 (General)

(800) 521-3168 (Technical)

(800) 272-4620 (Customer Service)

In Canada:

CRC Canada Co.

2-1246 Lorimar Drive

Mississauga, Ontario L5S 1R2

[www.crc-canada.ca](http://www.crc-canada.ca)

1-905-670-2291

In Mexico:

CRC Industries Mexico

Av. Benito Juárez 4055 G

Colonia Orquídea

San Luís Potosí, SLP CP 78394

[www.crc-mexico.com](http://www.crc-mexico.com)

52-444-824-1666

24-Hr Emergency – CHEMTREC: (800) 424-9300 or (703) 527-3887

---

---

## Section 2: Hazards Identification

---

---

### Emergency Overview

As defined by OSHA's Hazard Communication Standard, this product is hazardous.

Appearance & Odor: Silver semi-solid paste with petroleum odor

### Potential Health Effects:

**ACUTE EFFECTS:**

**EYE:** May cause irritation.

**SKIN:** For hypersensitive persons, may irritate the skin after prolonged periods of time.

**INHALATION:** Viscous nature may block breathing passages if inhaled.

**INGESTION:** May cause diarrhea.

**CHRONIC EFFECTS:** None known

**TARGET ORGANS:** None known

Medical Conditions Aggravated by Exposure: pre-existing skin sensitivities

See Section 11 for toxicology and carcinogenicity information on product ingredients.

**Product Name: Nickel Anti-Seize and Lubricating Compound**

**Product Number (s): SL 35911, SL35913**

---

---

### **Section 3: Composition/Information on Ingredients**

---

---

COMPONENT	CAS NUMBER	% by Wt.
Petroleum Oil	64742-57-0 / 64742-52-5	60 - 70
Graphite blend	82980-54-9 / 7782-42-5	10 - 20
Nickel powder	7440-02-0	20 - 30

---

---

### **Section 4: First Aid Measures**

---

---

**Eye Contact:** Immediately flush with plenty of water for 15 minutes. Call a physician if irritation persists.

**Skin Contact:** Remove contaminated clothing and wash affected area with soap and water. Call a physician if irritation persists. Wash contaminated clothing prior to re-use.

**Inhalation:** Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult give oxygen. Call a physician.

**Ingestion:** Wash out mouth immediately. Consult physician.

*Note to Physicians:* Treat symptomatically.

---

---

### **Section 5: Fire-Fighting Measures**

---

---

**Flammable Properties:** This product is not flammable at ambient temperatures.

Flash Point: 430°F (COC)	Upper Explosive Limit: 7.0
Autoignition Temperature: > 500°F	Lower Explosive Limit: 0.9

**Fire and Explosion Data:**

**Suitable Extinguishing Media:** Foam, dry powder, Halon®, carbon dioxide, sand, earth and water mist. Do not use water jet.

**Products of Combustion:** Smoke, soot, hydrocarbons, oxides of carbon, and possible metal carbonyls

**Explosion Hazards:** Containers, when exposed to heat from fire, may build pressure and rupture.

**Protection of Fire-Fighters:** Firefighters should wear self-contained, NIOSH-approved breathing apparatus for protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Use water spray to keep fire-exposed containers cool and to knock down vapors which may result from product decomposition.

---

---

### **Section 6: Accidental Release Measures**

---

---

**Personal Precautions:** Use personal protection recommended in Section 8.

**Environmental Precautions:** Take precautions to prevent contamination of ground and surface waters. Do not flush into sewers or storm drains.

**Methods for Containment & Clean-up:** Dike area to contain spill. Ventilate the area with fresh air. If in confined space or limited air circulation area, clean-up workers should wear appropriate respiratory protection. Scrape up bulk, then wipe up remainder with cloth. To

**Product Name: Nickel Anti-Seize and Lubricating Compound**

**Product Number (s): SL 35911, SL35913**

prevent walking hazard, pick up remaining residue with diatomaceous earth.

---

---

**Section 7: Handling and Storage**

---

---

Handling Procedures: Do not use near sources of ignition. Provide adequate ventilation during use. Wear appropriate personal protective equipment. For product use instructions, please see the product label.

Storage Procedures: Store in a cool dry area out of direct sunlight. Containers should be tightly closed while in storage. Keep out of reach of children and pets.

Aerosol Storage Level: NA

---

---

**Section 8: Exposure Controls/Personal Protection**

---

---

**Exposure Guidelines:**

COMPONENT	OSHA		ACGIH		OTHER		UNIT
	TWA	STEL	TWA	STEL	TWA	SOURCE	
Petroleum oil	5*	NE	5*	NE	NE		mg/m <sup>3</sup>
Graphite blend	2.5 (v)	NE	2	NE	2.5	NIOSH	mg/m <sup>3</sup>
Nickel powder	1	NE	1.5	NE	0.015	NIOSH	mg/m <sup>3</sup>
N.E. – Not Established      (c) – ceiling      (s) – skin      (v) – vacated      * – oil mist							

**Controls and Protection:**

Engineering Controls: Area should have ventilation to provide fresh air. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at the source, preventing dispersion into the general work area. Use mechanical means if necessary to maintain vapor levels below the exposure guidelines. If working in a confined space, follow applicable OSHA regulations.

Respiratory Protection: None required for normal work where adequate ventilation is provided. If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with organic vapor cartridge. Air monitoring is needed to determine actual employee exposure levels. Use a self-contained breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as nitrile or PVC. Also, use full protective clothing if there is prolonged or repeated contact of liquid with skin.

---

---

**Section 9: Physical and Chemical Properties**

---

---

Physical State: semi-solid paste  
Color: silver  
Odor: petroleum  
Odor Threshold: ND  
Specific Gravity: 1.24  
Initial Boiling Point: ND  
Freezing Point: ND  
Vapor Pressure: < 0.01 kPa  
Vapor Density: > 5 (air = 1)

**Product Name: Nickel Anti-Seize and Lubricating Compound**

**Product Number (s): SL 35911, SL35913**

Evaporation Rate: very slow

Solubility: negligilbe in water

Coefficient of water/oil distribution: ND

pH: NA

Volatile Organic Compounds: wt %: 0 g/L: 0 lbs./gal: 0

---

---

**Section 10: Stability and Reactivity**

---

---

Stability: Stable

Conditions to Avoid: Sources of ignition, temperature extremes

Incompatible Materials: Strong inorganic and organic acids, oxidizing agents

Hazardous Decomposition Products: Smoke, airborne soot, hydrocarbons, oxides of carbon and possible metal carbonyls

Possibility of Hazardous Reactions: No

---

---

**Section 11: Toxicological Information**

---

---

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

**Acute Toxicity:**

<u>Component</u>	<u>Oral LD50 (rat)</u>	<u>Dermal LD50 (rabbit)</u>	<u>Inhalation LC50 (rat)</u>
Petroleum oil	No data	No data	No data
Graphite blend	No data	No data	No data
Nickel powder	No data	No data	No data

**Chronic Toxicity:**

<u>Component</u>	<u>OSHA Carcinogen</u>	<u>IARC Carcinogen</u>	<u>NTP Carcinogen</u>	<u>Irritant</u>	<u>Sensitizer</u>
Petroleum oil	No	No	No	Unknown	Unknown
Graphite blend	No	No	No	Unknown	Unknown
Nickel powder	No	Group 2B	Reasonably anticipated to be a carcinogen	Unknown	Unknown

E – Eye      S – Skin      R - Respiratory

Reproductive Toxicity: No information available

Teratogenicity: No information available

Mutagenicity: No information available

Synergistic Effects: No information available

---

---

**Section 12: Ecological Information**

---

---

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity: No information available

Persistence / Degradability: No information available

Bioaccumulation / Accumulation: Bioaccumulation potential nil.

Mobility in Environment: Highly unlikely to cause widespread contamination.

**Product Name: Nickel Anti-Seize and Lubricating Compound**

**Product Number (s): SL 35911, SL35913**

---

---

## **Section 13: Disposal Considerations**

---

---

**Waste Classification:** This product is not a RCRA hazardous waste. (See 40 CFR Part 261.20 – 261.33)  
Empty containers may be recycled.

All disposal activities must comply with federal, state, provincial and local regulations. Local regulations may be more stringent than state, provincial or national requirements.

---

---

## **Section 14: Transport Information**

---

---

US DOT (ground): Not Regulated

ICAO/IATA (air): Not Regulated

IMO/IMDG (water): Not Regulated

Special Provisions: None

---

---

## **Section 15: Regulatory Information**

---

---

### **U.S. Federal Regulations:**

#### Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

#### Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: nickel (100 lbs)

**Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.**

#### Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories:	Fire Hazard	No
	Reactive Hazard	No
	Release of Pressure	No
	Acute Health Hazard	Yes
	Chronic Health Hazard	Yes

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:  
Nickel (< 30%)

#### Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): Nickel

### **U.S. State Regulations:**

#### California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm: Nickel

**Product Name: Nickel Anti-Seize and Lubricating Compound**

**Product Number (s): SL 35911, SL35913**

---

Consumer Products VOC Regulations: This product is not regulated.

State Right to Know:

New Jersey: 7440-02-0, 7782-42-5  
Pennsylvania: 7440-02-0, 7782-42-5  
Massachusetts: 7440-02-0, 7782-42-5  
Rhode Island : 7440-02-0, 7782-42-5

**Canadian Regulations:**

Controlled Products Regulations:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Hazard Class: D2A, D2B

Canadian DSL Inventory: All ingredients are either listed on the DSL Inventory or are exempt.

**European Union Regulations:**

RoHS Compliance: This product is compliant with Directive 2002/95/EC of the European Parliament and of the Council of 27 January 2003. This product does not contain any of the restricted substances as listed in Article 4(1) of the RoHS Directive.

**Additional Regulatory Information:** None

---


---

**Section 16: Other Information**

---

---

HMIS® (II)	
Health:	1
Flammability:	1
Reactivity:	0
PPE:	B



Ratings range from 0 (no hazard) to 4 (severe hazard)

Prepared By: Michelle Rudnick  
CRC #: SL35911  
Revision Date: 08/31/2011

Changes since last revision: MSDS reformatted to meet the requirements of the Canadian Controlled Products Regulations.

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this MSDS consult your supervisor, a health & safety professional, or CRC Industries.

**Product Name: Nickel Anti-Seize and Lubricating Compound**

**Product Number (s): SL 35911, SL35913**

---

ACGIH: American Conference of Governmental Industrial Hygienists	NA: Not Applicable
CAS: Chemical Abstract Service	ND: Not Determined
CFR: Code of Federal Regulations	NIOSH: National Institute of Occupational Safety & Health
DOT: Department of Transportation	NFPA: National Fire Protection Association
DSL: Domestic Substance List	NTP: National Toxicology Program
g/L: grams per Liter	OSHA: Occupational Safety and Health Administration
HMIS: Hazardous Materials Identification System	PMCC: Pensky-Martens Closed Cup
IARC: International Agency for Research on Cancer	PPE: Personal Protection Equipment
IATA: International Air Transport Association	ppm: Parts per Million
ICAO: International Civil Aviation Organization	RoHS: Restriction of Hazardous Substances
IMDG: International Maritime Dangerous Goods	STEL: Short Term Exposure Limit
IMO: International Maritime Organization	TCC: Tag Closed Cup
lbs./gal: pounds per gallon	TWA: Time Weighted Average
LC: Lethal Concentration	WHMIS: Workplace Hazardous Materials Information System
LD: Lethal Dose	