

NEER Zinc Bushed Conduit Nipples

CNN: Zinc

Applications

- Use through knockout to connect box to conduit coupling.
- Use with a locknut to connect two boxes side by side or back to back.
- Use with a locknut to connect fixture housings to continuous runs.

Features

- Male hub threads — NPS.
- Available with insulated throat.

Material/Finish

- Zinc die cast

Certifications and Compliances

- UL Standard: 514B
- UL Listed: E14814
- CSA Standard: C22.2 No. 18
- CSA Certified: 065178
- NEMA: FB-1



CNI-100

| Trade Size (Inches) | Catalog Number | Dimensions in Inches/Millimeters | |
|---------------------------------|-------------------|----------------------------------|----------------|
| | | Maximum Diameter | Body Length |
| Without Insulated Throat | | | |
| 1/2 | CNN-100 | 0.94/23.9 | 0.59/15.0 |
| 3/4 | CNN-200 | 1.19/30.2 | 0.72/18.3 |
| 1 | CNN-300 | 1.38/35.1 | 0.85/21.6 |
| 1-1/4 | CNN-400 | 1.74/44.2 | 0.87/22.1 |
| 1-1/2 | CNN-500 | 2.12/53.8 | 0.90/22.9 |
| 2 | CNN-600 | 2.55/64.8 | 1.15/29.2 |
| 2-1/2 | CNN-700 | 3.21/81.5 | 1.43/36.3 |
| 3 | CNN-800 | 3.80/96.5 | 1.43/36.3 |
| 3-1/2 | CNN-900 | 4.27/108.5 | 1.43/36.3 |
| 4 | CNN-1000 | 4.79/121.7 | 1.43/36.3 |

| Trade Size (Inches) | Catalog Number | Dimensions in Inches/Millimeters | |
|------------------------------|----------------|----------------------------------|----------------|
| | | Maximum Diameter | Body Length |
| With Insulated Throat | | | |
| 1/2 | CNI-100 | 0.94/23.9 | 0.67/17.0 |
| 3/4 | CNI-200 | 1.19/30.2 | 0.80/20.3 |
| 1 | CNI-300 | 1.38/35.1 | 0.93/23.6 |
| 1-1/4 | CNI-400 | 1.74/44.2 | 0.95/24.1 |
| 1-1/2 | CNI-500 | 2.12/53.8 | 0.98/24.9 |
| 2 | CNI-600 | 2.55/64.8 | 1.23/31.2 |

COMMERCIAL PRODUCTS: RIGID AND IMC FITTINGS

Commercial Products