



Product Number: 50340

Order Abbreviation: QTP 2X40TT5/120 PSN F

General Description: 2 lamp 120V 10 percent THD programmed rapid start normal ballast factor electronic ballast in an F enclosure size for FT40TT5 lamp

Product Information

Abbrev. With Packaging Info.	QTP2X40TT5120PSNF 20/CS 1/SKU
Ballast Factor	0.88
Ballast Height H (in)	1.0000
Ballast Length L (in)	9.5000
Ballast Width W (in)	1.6000
Circuit Type	Series
Family Brand Name	QUICKTRONIC Professional
Input Current (Amps)	0.00
Nominal Voltage (V)	120V
Number of Lamps	2
Power Factor	>0.97
Primary Lamp Type	FT40DL
Sound Rating	A
Starting Method	Programmed Start
Starting Temperature - Fahrenheit	0
Starting Temperature - Celsius	-18
Total Harmonic Distortion (THD)	<10%
Wiring Method	Leads



Footnotes

- Data based on primary lamp types. See LEDVANCE System Performance Guide for data on other lamp combinations.
- Remote Mounting up to 10 feet
- 70C Max Case Temperature
- UL Listed Class P, Type 1 Outdoor
- Ground ballast case
- Install in accordance with National Electric Codes
- Complies with FCC 47 CFR Part 18, Non-Consumer
- ANSI 62.41 Cat. A Transient Protection
- Class A Sound Rating.
- Minimum Starting Temperature: 0F/-18C.
- Input Frequency: 60Hz.