

OSR-PI

120V Preassembled Self-Regulating Heating Cable for Pipe Tracing for Freeze Protection and Roof and Gutter De-icing



eltherm[®]
innovations in heat tracing



Features

Nominal voltage

- 120V.

Cold lead length

- 36" (0.9 m).

Outer jacket

- Thermoplastic.

Bus wire

- Nickel plated copper.

Maximum operating temperature (power on)

- 60 °C (140 °F).

Maximum operating temperature (power off)

- 80 °C (176 °F).

Cable section

- 14.1 mm X 5.6 mm.

Bending radius, minimum

- 25 mm (1 in.).

Minimum installation and start-up temperature

- -25 °C (-13 °F).

Standards

- CSA C22.2.130.03; -WS.
- CAN/CSA 60079-7:12, 60079-0-11.
- ANSI/IEEE 515, 515.

Certification

- CSA C US 2547790

Rating

- Wet rated, for outdoor use (WS).

Warranty

- 1-year basic warranty on the heating cable.

Application

- Freeze protection, roof and gutter, pipes, vessel and tanks, sprinkler systems.

Models

Product #	Price	Length		Nominal power output in air condition at 5 °C (40 °F) ¹
		ft.	m	
ECK-7AO-006	108.00	6	1.8	42
ECK-7AO-012	125.00	12	3.6	84
ECK-7AO-018	151.00	18	5.5	126
ECK-7AO-025	176.00	25	7.6	175
ECK-7AO-050	262.00	50	15.2	350
ECK-7AO-075	321.00	75	22.9	525
ECK-7AO-100	436.00	100	30.5	700

¹ Because of the cable's self-regulating properties, the power density can reach up to 11 Watts per foot when buried in snow or ice: "wet density". In this situation, use of a 15 Amp. circuit breaker is valid for all models.

Linear power output in air condition according to operating temperature

