

**Product datasheet**  
Characteristics

# CD222N

60A 2P Type1 120/240VAC General Duty Safety Switch with Solid Neutral



## Main

Product or component type	Single Throw Safety Switch
Series name	General duty

## Complementary

[In] rated current	60 A
Disconnecter device type	Fusible disconnect
Short-circuit current	Cartridge 100 kA (maximum)
Device mounting	Surface
Number of poles	2
Electrical connection	Lugs
[Ue] rated operational voltage	120/240 V AC
AWG gauge	AWG 14...AWG 3 (copper or aluminium)

## Environment

product certifications	CSA
NEMA degree of protection	NEMA 1 galvanized steel

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1313 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.