



Main

Range of product	Square D
Product or component type	Single Throw Safety Switch
Line Rated Current	30 A
NEMA degree of protection	NEMA 3R/12 galvanized steel
Maximum Horse Power Rating	15 Hp 480 V AC 20 hp 600 V AC
Disconnecter device type	Fusible disconnect
Maximum short-circuit current	200 KA 10 kA
Device mounting	Surface
Number of poles	3
Phase	3 phase
Product certifications	CSA
[Ue] rated operational voltage	600 V AC/DC
AWG gauge	AWG 12...AWG 2 aluminium AWG 14...AWG 2 copper
Wiring configuration	4-wire

Complementary

Width	191.77 mm (7.55 in)
Height	370.84 mm (14.6 in)
Depth	125.98 mm (4.96 in)
Tightening torque	5.08 N.M (45 lbf.in) 0.02 in ² (13.3 mm ²) AWG 6) 4.52 N.M (40 lbf.in) 0.01 in ² (8.367 mm ²) AWG 8) 3.95 N.m (35 lbf.in) 0.00...0.01 in ² (2.06...5.21 mm ²) AWG 14...AWG 10)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.