



### Main

Range	Acti 9
Product name	Acti 9 iIL
Product or component type	Modular pilot light
Device short name	IIL
[Us] rated supply voltage	110...230 V AC at 50/60 Hz 110...130 V DC

### Complementary

Local signalling	1 LED green, 100000 h 0.3 W
Mounting mode	Fixed
Mounting support	Symmetrical DIN rail
Comb busbar and distribution block compatibility	Upside: ProDis
9 mm pitches	2
Height	3.23 in (82 mm)
Width	0.71 in (18 mm)
Depth	2.74 in (69.5 mm)
Color	White (RAL 9003)
Auxiliary connection terminal	Tunnel type terminal 1 rigid 0.00 in <sup>2</sup> (0.5 mm <sup>2</sup> ) Tunnel type terminal 2 rigid 0.00 in <sup>2</sup> (2.5 mm <sup>2</sup> ) Tunnel type terminal 1 flexible 0.00 in <sup>2</sup> (0.5 mm <sup>2</sup> ) Tunnel type terminal 2 flexible 0.00 in <sup>2</sup> (2.5 mm <sup>2</sup> ) Tunnel type terminal 2 flexible with ferrule 0.00 in <sup>2</sup> (2.5 mm <sup>2</sup> )
Wire stripping length	0.35 in (9 mm)
Tightening torque	8.85 lbf.in (1 N.m)

### Environment

Standards	IEC 60947-5-1
IP degree of protection	IP2 IPxx B
Pollution degree	3
Tropicalisation	2
Relative humidity	95 % 131 °F (55 °C)
Ambient air temperature for operation	-31...158 °F (-35...70 °C)
Ambient air temperature for storage	-40...176 °F (-40...80 °C)

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

---

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Halogen content performance	Halogen free plastic parts & cables product

---