

Photoelectric Sensor

12100RDS7250



General Description

Photoelectric Sensor, Comet, Through Beam, Right Angle, Output ON, 6.6 ft, 300 mA AC/DC at 20-264 Vac/15-30 Vdc, PVC, AC: L1 switched, DC: NPN open collector, 20-264 Vac 50/60 Hz, 15-30 Vdc (NPN)

Warranty

3 Years

Product Specifications

Package: 5.000 x 0.381 x 6.000 in.

Package Weight: 1.750 lbs.

- AC: L1 switched, DC: NPN open collector
- Polyurethane Foam (RIM)
- 300 mA
- 300 mA
- -4°-158° F
- Comet
- NEMA 1, 3, 4, 4X, 6, 12, 13, IP69k
- Auto reset S/C
- Auto reset S/C
- Through Beam
- 6.6 ft
- 20-264 Vac 50/60 Hz, 15-30 Vdc (NPN)
- 300 mA AC/DC at 20-264 Vac/15-30 Vdc
- Output ON
- PVC
- Right Angle



Powering Business Worldwide

Eaton
1000 Eaton Boulevard
Cleveland, OH 44122
United States
Eaton.com

© 2014 Eaton
All Rights Reserved
Printed in USA
August 2014

Eaton is a registered trademark.

All other trademarks are property of their respective owners.