



Powering Business Worldwide

pe.eaton.com

D3 General Purpose Relay

D3PF2AA1

UPC:782113720111

Dimensions:

- **Height:** 1.39 IN
- **Length:** 2.2 IN
- **Width:** 1.3 IN

Weight: .22 LB

Warranties:

- Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- **Coil Voltage:** 110 Vdc
- **Contact Configuration:** DPDT
- **Contact Material:** Silver alloy
- **Contact Rating:** 16A
- **Cover:** Full featured
- **Enclosure:** IP40
- **Maximum Voltage:** 300V switching
- **Options:** LED test button, flag indicator, lock-down door, finger-grip cover, ID tag
- **Series:** D3 series
- **Terminals:** Octal

Supporting documents:

- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions](#)
- [D3_F2 2D PDF](#)
- [D3_F2 2D Drawing Xchange](#)
- [D3_F2 3D Model Xchange](#)
- [D3_F2 3D Inventor](#)
- [D3_F2 AutoCAD 2D Footprint](#)
- [D3_F2 AutoCAD 2D Footprint \(mm\)](#)



- [Eaton Specification Sheet - D3PF2AA1](#)

Certifications:

- cRUus
- UL Listed
- CSA Certified

Product compliance:

- CE Marked
- RoHS Compliant

© 2016 Eaton. All rights reserved.