



**BURNDY Catalog Number**  
**UPC Number**  
**Description**  
**Status**

YA6CL2TC14E1  
 7818100184533  
 CU HYLUG-6STR-1/4X1INC-C  
 Active

**Web Use**  
 BURNDY Product Line

Tongue Angle  
 Length (in)  
 Tongue Type  
 Barrell Style  
 Bolt Hole Size (in)  
 Barrel Type  
 Thickness  
 B Length (in)  
 Pad Width (in)  
 E - in  
 Strip Length

**Dimensional**

Straight  
 2.44  
 Standard  
 Chamfered,Skived  
 0.27  
 Standard  
 0.08  
 0.54  
 0.45  
 1.00  
 5/8

Number of Holes  
 Product Description

**General**

2  
 Copper Compression Lug, 2 Hole  
 w/ Inspection Window, 6 AWG,  
 1/4" Stud, 1" Stud Hole Spacing,  
 Short Barrel, Tin - Electro Plated

Flex (Class G) Size - Range  
 Flex (Class H) Size - Range  
 Flex (Class I) Size - Range  
 Copper Solid Size (Range)  
 DLO Size (Range)  
 Copper Stranded (Range)

**Conductor(s)**

N/A  
 N/A  
 N/A  
 N/A  
 N/A  
 6 AWG

Type of Plating  
 Bolt Hole Size  
 Color Code  
 Plated (Yes or No)  
 Index Number  
 Product Material

**Physical**

Tin - Electro Plated  
 1/4  
 Blue  
 Y  
 7,374  
 Copper

UL Listed  
 CSA Certified  
 ROHS Compatible  
 UL Recognized  
 CULUS  
 Industry Standards

**Approvals / Certifications**

Y  
 Y  
 Compliant  
 N  
 N  
 UL468A-468B

**Documentation**

**For further technical assistance, please contact us**

**BURNDY LLC - USA**

47 East Industrial Park Drive  
 Manchester NH 03109

**BURNDY Technical Services**

47 East Industrial Park Drive  
 Manchester NH 03109

Hours: 8:00 AM - 5:00 PM  
 Monday - Friday  
 Phone: 800-346-4175