

LJA36400U33X

POWERPACT L-FRAME, I-LINE CIRCUIT BREAKER, MICROLOGIC 3.3S, 400A, 3P, 600V, 25kA



Product availability: Stock - Normally stocked in distribution facility



Main

Product or component type	Circuit breaker
Range of product	PowerPact L
Trip Unit Type	Electronic, standard, Micrologic 3.3 S, LSI
Interrupt Code	J

Complementary

Protection technology	Current limiter
Line Rated Current	400 A
Number of Poles	3P
Interrupt Rating	65 KA 480 V AC 100 KA 240 V AC 25 kA 600 V AC
Voltage Rating	600 V AC
Continuous current rating	80 %
Mounting mode	I-Line
Electrical connection	I-Line connection line Lugs load
Wire Size	AWG 3/0...500 kcmil aluminium/copper)2
Terminal Type	AL600LF52K3
I-Line Phase Connection	ABC
Height	373.38 mm (14.7 in)
Width	150.88 mm (5.94 in)
Depth	167.89 mm (6.61 in)
Tightening torque	38.94...442.54 Lbf.in (4.4...50 N.m) 0.15...0.37 in ² (95...240 mm ²) AWG 3/0...500 kcmil) 38.94...442.54 lbf.in (4.4...50 N.m) AWG 3/0...500 kcmil)

Environment

Product certifications	UL listed CSA NMX CE CCC
------------------------	--------------------------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ordering and shipping details

Category	01118 - L ELEC TRIP I-LINE BREAKER/SW
Discount Schedule	DE2
GTIN	00785901807957
Package weight(Lbs)	8.71 kg (19.2 lb(US))
Returnability	Yes
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------