

## 596-00252

**Article Number: 596-00252**

**Solar Label, AC Module Printable Solar Label, 4.0" X 2.0", Vinyl, Red, 50/RL**



### Base Data

**Local Order Number** 596-00252

**Type** AC2011

**Color** Red (RD)

**Features and Benefits**

- Made with UV stable inks and materials for durability and weather resistance.
- The labels are supplied with aggressive adhesive to ensure long life.
- Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

**Application Solarenergy** Solar Installation Labels are used to mark residential and commercial solar panel installations on schools, buildings, homes and farms with the most common labels required by NEC 2014 and the IFC 2012 as well as Cal Fire. Labels for marking EMT conduit as well as disconnects, combiner boxes and breaker panels are all part of the selection offered by HellermannTyton.

**Color of Print** White (WH)

**Product Description** HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

**Technical Description** 4" X 2" White text on red background that reads as: "NOMINAL AC VOLTAGE;NOMINAL OPERATING AC FREQUENCY;MAXIMUM AC POWER;MAXIMUM AC CURRENT;MAXIMUM OVERCURRENT DEVICE RATING FOR AC MODULE PROTECTION." 50 per roll. Label is also printable using a thermal transfer printer to add the variable voltage information on demand.

**Short Description** Solar Label, AC Module Printable Solar Label, 4.0" X 2.0", Vinyl, Red, 50/RL

### Product Dimensions

**Width W (imperial)** 4.0 "

**Width W (metric)** 101.6 mm

**Height H (imperial)** 2.0 "

**Height H (metric)** 50.8 mm

### Logistics and Packaging

**Quantity per** roll

**Package Quantity** 50

### Material and Specifications

<b>Material</b>	Vinyl
<b>Material Shortcut</b>	Vinyl
<b>Shortcut Adhesive</b>	Acryl
<b>Adhesive</b>	Acrylic
<b>Adhesive Operating Temperature</b>	-40 °F to +180 °F (-40 °C to +82 °C)
<b>Halogenfree</b>	YES
<b>Material Specification</b>	HF
<b>Operating Temperature</b>	-40 °F to +302 °F (-40 °C to +150 °C)
<b>Recommended Ribbon Type</b>	TT822OUT
<b>ROHS Conformity</b>	Yes
<b>UL Recognized (US)</b>	Yes

---

© HellermannTyton 2014