

Specification Sheet

Part Number: 596-00613

**CAUTION: SOLAR ELECTRIC
SYSTEM CONNECTED**

Solar Label, Reflective, CAUTION SOLAR ELECTRIC SYSTEM CONNECTED, 6.5" x 1.0", Yellow, 50/roll

Article Number	596-00613
Type	CSESC
Color	Yellow (YE)
Features & Benefits	<ul style="list-style-type: none">• Made with UV stable inks and materials for durability and weather resistance• Supplied with aggressive adhesive to ensure long life• Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections• Pre-printed labels offer significant time and cost savings over high priced engraved and lead time purchased markers
Quantity Per	roll

Product Description

HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description

Solar Label, Reflective, CAUTION SOLAR ELECTRIC SYSTEM CONNECTED, 6.5" x 1.0", Yellow, 50/roll

Global Part Name

CSESC-242/552-YE

Technical Description

Pre-Printed Solar Label, Reflective, "SOLAR ELECTRIC SYSTEM CONNECTED", 6.5" X 1.0", Yellow

Local Order Number 2

Cross Reference = 10 per pack: 596-00672; Spanish version 50 per roll: 596-00821

Width W (Imperial)

6.5

Width W (Metric)

165.1

Thickness T (Metric)

64.0

Height H (Imperial)

1.0

Height H (Metric)

25.4

Material

Type 242/552, UV Stable Reflective Vinyl w/Acrylic Laminate

Material Shortcut

242/552

Adhesive	Acrylic
Halogen free	No
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature (Metric)	-40°F to +174°F (-40°C to +79°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	NEC2011 NEC2014 UL 969 IFC 2012 ANSI Standard Z535.4
Warranty (US)	Yes
UL Recognized (US)	Yes
Package Quantity(Imperial)	50
Package Quantity (Metric)	50
Customs Number	3919905060
Labels per Column	1
Labels per Row	1
Weight (Metric)	.104
Weight (Imperial)	0.23

© 2018 HellermannTyton. All rights reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)