




**ENTRANCE HEADS - ALUMINUM**

Clamp Type for Rigid/IMC or EMT, Aluminum  
N/A

**B78**



Catalog #: 2414

**APPLICATIONS**

For use to bring overhead electrical service into buildings  
N/A

**PRODUCT FEATURES**

Lightweight aluminum body construction eases installation and provides corrosion resistance  
Plastic insuliner snaps out easily for quick cable insertion

**UL LISTED**

Standard 514B, UL Listed E195972, E195973

**GENERAL PRODUCT INFORMATION**

Trade Size: 3-1/2 in.

**CONFIGURATION**

Insulating Hole Diameter: 3 Holes 1-5/16 in. Dia.; 4 Holes 1-1/8 in. Dia.

**DRAWING DIMENSIONS**

Dimension A: 9-9/16 in.  
Dimension B: 7-7/64 in.  
Dimension C: 8-5/32 in.  
Dimension D: 13-1/16 in.

**PACKAGING**

Package Type: Carton  
Ship Carton Qty.: 1  
Product UPC-A Labeled: No  
Weight (Lbs. Per/C): 664.00  
Ship Carton Length (in.): 11.40  
Ship Carton Width (in.): 11.20  
Ship Carton Height (in.): 8.00  
Ctn Weight (Lbs.): 6.64  
UPC Number: 050169024140  
I2of5: 50050169024145