

Entrance Caps PC 5690

- UL Listed
- Die Cast Copper Free Aluminum
- Phenolic Insulator
- Clamp On Style
- Weather Resistant

Clamp on service entrance caps permit a weather resistant entrance for type SE cable on rigid, IMC or EMT for pulling service drop conductors. They are assembled with an electrical grade Phenolic insulator with multiple holes.



| CAT NO | UPC | SIZE | STD | MSTR | WT/STD | UNIT |
|--------|-------|--------|-----|------|--------|------|
| EC50 | 40005 | 1/2" | 25 | 25 | 6.21# | C |
| EC75 | 40010 | 3/4" | 25 | 25 | 7.18# | C |
| EC100 | 40015 | 1" | 25 | 25 | 8.97# | C |
| EC125 | 40020 | 1-1/4" | 10 | 10 | 4.89# | C |
| EC150 | 40025 | 1-1/2" | 10 | 10 | 7.56# | C |
| EC200 | 40030 | 2" | 5 | 5 | 6.09# | C |
| EC250 | 40035 | 2-1/2" | 1 | 1 | 3.83# | C |
| EC300 | 40040 | 3" | 1 | 1 | 5.43# | C |
| EC350 | 40045 | 3-1/2" | 1 | 1 | 6.47# | C |
| EC400 | 40050 | 4" | 1 | 1 | 6.78# | C |

Entrance Ells (SLB) PC 5700

- UL Listed
- Die Cast Copper Free Aluminum
- Assembled with Fiber Gasket & Aluminum Cover
- Weather Resistant

Service Entrance Ells are used with threaded rigid conduit or IMC for providing access to the interior of a conduit system for pulling, splicing, inspection and maintenance.



| CAT NO | UPC | SIZE | STD | MSTR | WT/STD | UNIT |
|--------|-------|--------|-----|------|--------|------|
| SLB50 | 40100 | 1/2" | 10 | 100 | 2.01# | C |
| SLB75 | 40105 | 3/4" | 10 | 100 | 2.60# | C |
| SLB100 | 40110 | 1" | 5 | 50 | 2.15# | C |
| SLB125 | 40115 | 1-1/4" | 5 | 50 | 3.76# | C |
| SLB150 | 40120 | 1-1/2" | 2 | 20 | 1.83# | C |
| SLB200 | 40125 | 2" | 2 | 10 | 2.69# | C |

Pulling Ells PC 5710

- UL Listed
- Die Cast
- High Strength Zinc Alloy
- Removable Aluminum Cover & Neoprene Gasket

Pulling Ells are used to connect two lengths of threaded rigid conduit or IMC to form a 90° bend and provide access for wire pulling.



| CAT NO | UPC | SIZE | STD | MSTR | WT/STD | UNIT |
|--------|-------|------|-----|------|--------|------|
| PE1 | 40130 | 1/2" | 10 | 100 | 1.89# | C |
| PE2 | 40135 | 3/4" | 10 | 100 | 2.69# | C |
| PE3 | 40140 | 1" | 5 | 25 | 2.50# | C |