



Nichols Manufacturing

541-485-6050
fax 541-485-3617

Pole Stand-offs

All of our stand-offs are hot dip galvanized per ASTM A-153 specifications.

All steel is per ASTM A-36 specifications. Welded construction.

Strut is 13/16-14GA steel. Sold by piece

Part #

MB3

5" stand-off.

Base is 1/4" x 1-1/2" x 8"

MB4

5" stand-off w/brace

Base is 1/4" x 1-1/2" x 8"

PSB12

12" stand-off w/brace

PSB15

15" stand-off w/brace

PSB18

18" stand-off w/brace

SOS8

8" stand-off, crescent

SOS12

12" stand-off, crescent

SOS15

15" stand-off, crescent

SOS18

18" stand-off, crescent

SOS24

24" stand-off, crescent

SOD8

8" stand-off, diamond

SOD12

12" stand-off, diamond

SOD15

15" stand-off, diamond

SOD18

18" stand-off, diamond

SOD24

24" stand-off, diamond

SDT's come with 8" T at end of strut, 12" and 16" T's are also available

SDT0

0" stand-off w/T, diamond

SDT4

4" stand-off w/T, diamond

SDT6

6" stand-off w/T, diamond

SDT8

8" stand-off w/T, diamond

SDT12

12" stand-off w/T, diamond

SDT15

15" stand-off w/T, diamond

SDT18

18" stand-off w/T, diamond

