

Set-Screw Rigid Connectors & Couplings

For Threadless Rigid Conduit & IMC

Type 28

Use:

To connect threadless rigid conduit to boxes and enclosures.

Features:

- Concretetight.
- Available with insulated throat.
- Male hub thread (NPS)

Material/Finish:

Malleable Iron/Zinc Plated

Optional Finish:

- ½" - 1½" Mechanically Galvanized
- 2" - 6" Hot Dip Galvanized

Contact your local representative for pricing and availability.


Third Party Certification:




Applicable Third Party Standards:

UL Standard: 514B
Fed. Spec./CID: A-A-50553
ANSI/NEMA: FB-1

Trade Size (inches)	Catalog Number	Insulated Throat Catalog Number	Dimensions in Inches		
			Body Length	Max Dia.	Thread Length
½	28-050	28-050T	3 ¹ / ₃₂	1¼	7 ¹ / ₁₆
¾	28-075	28-075T	1 ¹ / ₁₆	1 ¹ / ₁₆	7 ¹ / ₁₆
1	28-100	28-100T	1 ¹ / ₁₆	1¾	1 ¹ / ₃₂
1¼	28-125	28-125T	1 ¹ / ₁₆	2½	5 ¹ / ₈
1½	28-150	28-150T	1¾	2¾	5 ¹ / ₈
2	28-200	28-200T	1 ⁷ / ₈	2¾	5 ¹ / ₈
2½	28-250	28-250T	2 ¹ / ₈	3 ³ / ₁₆	1
3	28-300	28-300T	2 ⁵ / ₈	4¼	1
3½	28-350	28-350T	2¾	4¾	1 ¹ / ₈
4	28-400	28-400T	3	5¼	1 ¹ / ₈
5	28-500	28-500T	4	6¾	1¼
6	28-600	28-600T	4½	7 ¹ / ₈	1¼



Type 28-050 — Type 28-200



Type 28-250 — Type 28-600

Type 29

Use:

To couple sections of threadless rigid conduit together.

Features:

- Concretetight

Material/Finish:

Malleable Iron/Zinc Plated

Optional Finish:

- ½" - 1½" Mechanically Galvanized
- 2" - 6" Hot Dip Galvanized

Contact your local representative for pricing and availability.


Third Party Certification:




Applicable Third Party Standards:

UL Standard: 514B
Fed. Spec./CID: A-A-50553
ANSI/NEMA: FB-1

Trade Size (inches)	Catalog Number	Dimensions in Inches	
		Length	Max. Dia.
½	29-050	1¾	1¼
¾	29-075	2 ¹ / ₈	1 ¹ / ₁₆
1	29-100	2 ⁵ / ₈	1¾
1¼	29-125	2¾	2 ¹ / ₈
1½	29-150	3 ¹ / ₈	2 ³ / ₈
2	29-200	3 ³ / ₈	2 ⁷ / ₈
2½	29-250	3 ⁷ / ₈	3 ³ / ₁₆
3	29-300	4 ³ / ₈	4 ¹ / ₃₂
3½	29-350	5	4¾
4	29-400	5½	5¼
5	29-500	7½	6¾
6	29-600	8½	7 ¹ / ₈



Type 29-050 — Type 29-200



Type 29-250 — Type 29-600