

PVIC - Single Pair & Triads

PVIC™ - Single Pair & Triads
Shielded & Non-Shielded
105°C - 300 Volt - PLTC/ITC

Instrumentation



*Product images are for illustrative purposes only and may differ from the actual product.

Applications:

- Cable is suitable for use in Class I Division II hazardous locations
- Cable is UL approved for sunlight resistant applications
- Cable is suitable for direct burial

Standards:

- UL listed as type PLTC & CL3 per UL standard 13
- Type ITC per UL standard 2250
- IEEE 1202 available upon request
- RoHS compliant

PART NUMBER TABLE

Part#	Gauge	Pairs	Triads	Insulation Thickness	Jacket Thickness	Outside Diameter Inches	Material Weight (Lbs./M')
K32202	22	1	0.013	0.04	0.193	20	
K32002	20	1	0.016	0.035	0.215	26	
K42003	20	1	0.016	0.035	0.217	32	
K11802	18	1	0.016	0.035	0.224	29	
K31802	18	1	0.016	0.035	0.226	34	
K41803	18	1	0.016	0.035	0.247	43	
K11602	16	1	0.016	0.035	0.247	38	
K31602	16	1	0.016	0.035	0.252	45	
K31602-05	16	1	0.016	0.035	0.254	46	
K41603	16	1	0.016	0.035	0.266	57	

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco •
Seattle • St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC