

Landscape Lighting, 150V Sunlight Resistant

Landscape Lighting - 60°C - 150V

Low Voltage Lighting



*Product images are for illustrative purposes only and may differ from the actual product.

Category Conductor Description:

- Stranded bare copper

Insulation:

- Black, sunlight- and moisture-resistant, Polyvinyl Chloride (PVC)

Applications:

- For use in low voltage outdoor lighting systems
- Used in outdoor security wiring

Standards:

- UL 758
- AWM Style 2363
- OSHA Acceptable

PART NUMBER TABLE

Part#	Gauge	Conductors	Stranding	Insulation Thickness	Outside Diameter Inches	Material Weight (Lbs./M')	Material Weight (KG/KM)
LV11402	14	2	41	0.045	.1700x.3540	48	71
LV11202	12	2	65	0.045	.1900x.3920	65	96
LV11002	10	2	19	0.045	.2810x.5960	90	133
LV10802	8	2	19	0.06	.3400x.6850	159	236

Note: The data shown are approximate and subject to standard industry and manufacturer tolerances.

Selling Exclusively Through Distribution Since 1977™ | phone: 800-292-OMNI | website: omnicable.com
Atlanta • Boston • Charlotte • Chicago • Cincinnati • Denver • Houston • Los Angeles • Philadelphia • San Francisco •
Seattle • St. Louis • Tampa • Toronto
© 2020 Omni Cable LLC