



LED B11

3.3B11/PER/927-922/CL/G/E26/WGX1FB T20

Philips LED B11 candles offer energy saving ambiance with the elegant effect of incandescent candles. These designs provides light in an omnidirectional manner, giving lighting designers a long life alternative to standard incandescent sources.

Product data

General Information	
Base	E26 [Single Contact Medium Screw]
Nominal Lifetime (Nom)	15000 h
Switching Cycle	20000X
Technical Type	3,3-40W

Light Technical	
Color Code	927-922 [CCT of 2700K-2200K]
Initial lumen (Nom)	300 lm
Luminous Flux (Rated) (Nom)	300 lm
Color Designation	Warm Glow(WG)
Correlated Color Temperature (Nom)	2700-2200 K
Luminous Efficacy (rated) (Nom)	90.00 lm/W
Color Consistency	<4
Color Rendering Index (Nom)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Power (Rated) (Nom)	3,3 W
Lamp Current (Nom)	35 mA
Wattage Equivalent	40 W
Starting Time (Nom)	0,5 s
Warm Up Time to 60% Light (Nom)	0,5 s

Power Factor (Nom)	0.75
Voltage (Nom)	120 V
Temperature	
T-Case Maximum (Nom)	50 °C


Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Bulb Finish	Clear

Product Data	
Order product name	3.3B11/PER/927-922/CL/G/E26/WGX1FB T20
EAN/UPC - Product	046677549589
Order code	549584
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929002047204
Net Weight (Piece)	0.016 kg

LED B11


Dimensional drawing




Candle B11 120V 4.5?-40W 300lm 2700-2200

Product	D	C
3.3B11/PER/927-922/CL/G/E26/WGX1FB T20	35 mm	92 mm


Photometric data



LEDbulb E12 E26 BA11 B11 927 CL-LDD



LEDbulb 3.3W E26 B11 927 CL




LEDbulb 927 CL-POC

LED B11

Lifetime



LEDbulb_15K LED



LEDbulb_15K LMP

