



Starlight LED lamps

ENERGY SAVINGS • 30,000 HOURS • 5 YEAR WARRANTY

Shine as bright as a star with our new LED Starlight series. The sleek, modern shape can be used in a wide variety of applications—from pendants to sockets and everywhere in between.

LIMITLESS OPTIONS FOR THE FOLLOWING APPLICATIONS

- Commercial
- Industrial
- Retail
- Residential

FEATURES

Up to 85% more efficient than incandescent/halogen replacements

Long life: 30,000 hours

Smooth warm dimming

UL approved for damp location

Sleek, low profile design

BENEFITS

Instant energy savings

Minimizes replacement and maintenance costs

Creates the perfect atmosphere

Can be used outdoors when protected from elements—withstands humidity indoors/outdoors

Unique shape for limitless applications

SPECIFICATIONS

Color Temperatures	3000K; 4000K; 5000K;
.....	3000K to 1800K
Input Line Voltage	120V
Input Line Frequency.....	50/60HZ
Lamp Life (Rated)	30,000 hours
Minimum Starting Temp	-22F/-30C
Maximum Operating Temp.....	45°C
CRI	80



5 YEAR WARRANTY
* Based on 12 hours use per day

RoHS COMPLIANT



SL13



SL16



SL19



SL22

we know light.™



Starlight Lamps

ENERGY SAVING • 30,000 HOURS • 5 YEAR WARRANTY

ITEM #	DESCRIPTION	VOLTAGE	LED WATTS	WATTAGE EQUIVALENT	LUMENS	LPW	CRI	COLOR TEMP	BEAM ANGLE	MOL (inches)	DIA (inches)	BASE
LED SL13 Starlight 65W Equivalent												
9W LED • 30,000 hours												
L9SL13D3030K	LED STARLIGHT DIM 9W 30K	120V	9	65	950	105.56	80	3000K	110°	3.8	5.2	E26
L9SL13D3040K	LED STARLIGHT DIM 9W 40K	120V	9	65	1000	111.11	80	4000K	110°	3.8	5.2	E26
L9SL13D3050K	LED STARLIGHT DIM 9W 50K	120V	9	65	1000	111.11	80	5000K	110°	3.8	5.2	E26
LED SL16 Starlight 100W Equivalent												
15W LED • 30,000 hours												
L15SL16D3030K	LED STARLIGHT DIM 15W 30K	120V	15	100	1625	108.33	80	3000K	110°	3.8	6.3	E26
L15SL16D3040K	LED STARLIGHT DIM 15W 40K	120V	15	100	1700	113.33	80	4000K	110°	3.8	6.3	E26
L15SL16D3050K	LED STARLIGHT DIM 15W 50K	120V	15	100	1750	116.67	80	5000K	110°	3.8	6.3	E26
L15SL16D30A	LED ALLUSION 15W WARM-DIMMING	120V	15	100	1750	116.67	80	3000K to 1800K	110°	3.8	6.3	E26
LED SL19 Starlight 140W Equivalent												
19W LED • 30,000 hours												
L19SL19D3030K	LED STARLIGHT DIM 19W 30K	120V	19	140	2100	110.53	80	3000K	110°	4.5	7.75	E26
L19SL19D3040K	LED STARLIGHT DIM 19W 40K	120V	19	140	2250	118.42	80	4000K	110°	4.5	7.75	E26
L19SL19D3050K	LED STARLIGHT DIM 19W 50K	120V	19	140	2250	118.42	80	5000K	110°	4.5	7.75	E26
LED SL22 Starlight 160W Equivalent												
22W LED • 30,000 hours												
L22SL22D3030K	LED STARLIGHT DIM 22W 30K	120V	22	160	2350	106.82	80	3000K	110°	4.8	8.9	E26
L22SL22D3040K	LED STARLIGHT DIM 22W 40K	120V	22	160	2450	111.36	80	4000K	110°	4.8	8.9	E26
L22SL22D3050K	LED STARLIGHT DIM 22W 50K	120V	22	160	2450	111.36	80	5000K	110°	4.8	8.9	E26
LED SL122 Starlight 200W Equivalent												
25W LED • 30,000 hours												
L25SL122HD3030K	LED STARLIGHT DIM 25W 30K HL	120V	25	200	3100	124.00	80	3000K	110°	4.8	8.9	E26

Custom colors are available by special order.

Matching Pendant Mounts are also available:

- 555PMB Pendant Mount Black
- 555PMWHT Pendant Mount White
- 555PMRED Pendant Mount Red
- 555PMGRN Pendant Mount Green
- 555PMBLU Pendant Mount Blue



RoHS
COMPLIANT

5 YEAR
WARRANTY

*Based on 12 hours use per day

For the most up-to-date specs, please visit www.tcp.com

TCP®

325 Campus Dr. | Aurora, Ohio 44202 | P: 800-324-1496 | tcp.com

©TCP JUN 2019/WF143350