

Blackburn® W™ Aluminum Service Wedge Clamps

Deadend self-supporting drop wire.

| Features | Benefits/Descriptions |
|--|--|
| Drop Wire May Be Cut to Exact Length | Adjustments in drop wire sag are easily made. This also saves the conductor. |
| Can Be Attached to Bare Neutral at Any Point in the Span | Place them where you most need them |
| Versatile Use | Flexible and rigid bails grip ACSR, AAC and AAAC conductors. |



Blackburn® W™ Aluminum Service Wedge Clamps

| CAT. NO. | Description | Conductor Range | | | Dimensions (in.) | | Typical Tensile Values | | Colour Code |
|--------------------|--|-----------------|-------------------|---------|------------------|--------|------------------------|-------------|-------------|
| | | ACSR | AL | AAAC | D | L | Conductor | Value (lb.) | |
| W62-1 | W-1 Series aluminum wedge and slider | #2-#6 | #1 str.-#6 sol. | #2-#6 | 2-3/8 | 12 | 2 (6/1) ACSR | 1,200 | Orange |
| W62-1 FC | | | | | flex. | 17-1/2 | | | |
| W20-1 | | 1/0-#4 | 2/0 str.-#2 sol. | 1/0-#4 | 2-3/8 | 12-1/2 | 1/0 (6/1) ACSR | 1,800 | Blue |
| W20-1 FC | | | | | flex. | 18-1/2 | | | |
| W40-1* | | 4/0-2/0 | 4/0 str.-2/0 sol. | 4/0-2/0 | 2-3/8 | 12-3/4 | 4/0 (6/1) ACSR | 1,900 | Red |
| W40-1 FC* | flex. | | | | 18-1/2 | | | | |
| W62-1 B† | W-1B Series iridized aluminum wedge and slider | 2-#6 | #1 str.-#6 sol. | 2-#6 | 2-3/8 | 12 | 2 (6/1) ACSR | 1,200 | Orange |
| W62-1 BFC† | | | | | flex. | 17-1/2 | | | |
| W20-1 B† | | 1/0-#4 | 2/0 str.-#2 sol. | 1/0-#4 | 2-3/8 | 12-1/2 | 1/0 (6/1) ACSR | 1,800 | Blue |
| W20-1 BFC† | | | | | flex. | 18-1/2 | | | |
| W40-1 B*† | | 4/0-2/0 | 4/0 str.-2/0 sol. | 4/0-2/0 | 2-3/8 | 12-3/4 | 4/0 (6/1) ACSR | 1,900 | Red |
| W40-1 BFC*† | flex. | | | | 18-1/2 | | | | |


* W40 series clamps rated 850 lb. ultimate tension for 1/0 ACSR, AL or AAAC.
† For extremely corrosive areas.

NOTE: Catalogue numbers with "FC" suffix have a flexible bail.

Blackburn® W™ Stainless Steel Wedge Clamp

The wedge clamp that stands up to corrosion.

| Features | Benefits/Descriptions |
|--|--|
| Stainless Steel Wedge and Slider | Rigid bail grips copper neutral conductors. |
| Drop Wire May Be Cut to Exact Length | Adjustments in drop wire sag are easily made. This also saves the conductor. |
| Can Be Attached to Bare Neutral at Any Point in the Span | Place them where you most need them. |



Blackburn® W™ Stainless Steel Wedge Clamp

| CAT. NO. | Conductor Range | | Dimension (in.) | | Typical Tensile Values | | Colour Code |
|----------|-----------------|-------|-----------------|----|------------------------|-------------|-------------|
| | Stranded | Solid | D | L | Conductor | Value (lb.) | |
| W62D | #2-#6 | #1-#6 | 2-3/8 | 12 | #2-#7 str. AAC | 1,300 | Orange |