


Touch-Plate 3000/3000-PL Relay




3000 Product Features

- Direct replacement for 1550-A, 1550-B, 2500-B, and 4000
- Loads connect into terminal block on the relay
- Maximum wire size is #10AWG
- Low voltage leads end in #20AWG

3000 Product Specifications

- Main Contact Configuration
 - Isolated SPST, Latching
 - Rating is 120/277VAC 20Amp 1.0HP 125VAC, 1.5HP 250VAC
- Coil Power Requirement
 - 0.044 Watts-Seconds pulsed 28.5VDC @ 0.020 seconds min to 0.100 secs max
- Coil Resistance
 - 7.2 OHMs + 10%; Duty Cycle 50% @ 1 second max
- Coil Temperature Rating
 - Max Operating temp of 65°C



3000-PL Product Features

- Direct replacement for 1550B-PL, 2500-BPL, and 4000-PL
- Loads connect into terminal block on the relay
- Low voltage leads end in female modular connector

3000-PL Product Specifications

- Main Contact Configuration
 - Isolated SPST, Latching
 - 120/277VAC 20Amp 1.0HP 125VAC, 1.5HP 250VAC
- Auxiliary Contact Configuration
 - SPST, Latching
 - 1A @ 30VAC
- Coil Power Requirement
 - 0.044 Watts-Seconds pulsed 28.5VDC @ 0.020 seconds min to 0.100 secs max
- Coil Resistance
 - 7.2 OHMs + 10%; Duty Cycle 50% @ 1 second max
- Coil Temperature Rating
 - Max Operating temp of 65°C

