


### Standard - Roof Jacks PC 5230

Roof Jacks are applied to the roof to form a water-tight seal. They add additional support between the roof line and service entrance conduit or ventilation pipe.

- 28 Gauge
- Galvanized Steel

CAT NO	UPC	SIZE	STD	MSTR	WT/STD	UNIT	
RJ50	69600	<b>Standard</b>	1/2"	24	24	24.08#	Ea
RJ75	69605		3/4"	24	24	23.92#	Ea
RJ100	69610		1"	24	24	23.06#	Ea
RJ125	69615		1-1/4"	24	24	23.13#	Ea
RJ150	69620		1-1/2"	24	24	22.87#	Ea
RJ200	69625		2"	24	24	21.82#	Ea
RJ300	69630		3"	12	12	15.22#	Ea
RJ400	69635		4"	12	12	19.39#	Ea



### 3 in 1 Roof Jacks PC 5250

Roof Jacks are applied to the roof to form a water-tight seal. They add additional support between the roof line and service entrance conduit or ventilation pipe.

- 24 Gauge
- Elastomer Collar

CAT NO	UPC	PIPE SIZE	STD	MSTR	WT/STD	UNIT
RN3	10350	Pipe Sizes: 1/2", 3/4", 1" * Base Size: 8-3/4", 12-1/2"	12	12	11.95#	Ea
RN4	10352	Pipe Sizes: 1-1/2", 2", 2-1/2", 3" Base Size: 10-3/4" x 12-1/2"	12	12	18.82#	Ea

\*Can be modified to fit 1-1/4" pipe      Fits any roof pitch - from flat to 45°      Tested for ultraviolet, ozone, and weather resistance.



### Steel / Galvanized - Tie Wire PC 5030 - 5035

Tie wire is used for many purposes, among them tying down PVC conduit in trenches before pouring concrete, as well as drop ceiling applications.

- 16 1/2 Gauge
- 400 Ft. (3 1/2#)
- Black Annealed or Galvanized

CAT NO	UPC	STD	MSTR	WT/STD	UNIT
<b>Black Annealed - PC 5030</b>					
TY164	28170	20	20	71.10#	Ea
<b>Galvanized - PC 5035</b>					
VTYG	28180	20	20	68.35#	Ea



### Tie Wire Dispenser PC 5040

The tie wire dispenser stores and dispenses tie wire.

- High Impact Plastic
- Mounts On Tool Belt

CAT NO	UPC	DESCRIPTION	STD	MSTR	WT/STD	UNIT
TYD	28175	Tie Wire Dispenser	1	6	1.10#	Ea

