


Compression Connectors

Insulating covers included.

Type PA — Pin Adapter Terminals

- Connector for aluminum conductor only
- Pigtail may be inserted into either aluminum or copper connectors
- 90° C rating per UL® 486B
- Tin-plated stranded copper wire pigtail
- Tin-plated aluminum barrel prefilled with oxide inhibitor and capped



CAT. NO.	CONDUCTOR SIZE	COPPER STUD SIZE	DIMENSIONS (IN.)			DIE COLOR CODE
			A	B	O.D.	
PA06	#6 Str. AWG	8	1/8	1 1/2	.640	N/A
PA04	#4 Str. AWG	6	1/8	1 1/2	.640	
PA02	#2 Str. AWG	4	7/8	1 1/2	.640	
PA01	#1 Str. AWG	3	1	1 1/2	.640	
PA11	1/0 Str. AWG	2	1 1/4	1 1/2	.906	RED
PA21	2/0 Str. AWG	1	1 7/8	1 1/2	.906	
PA31	3/0 Str. AWG	1/0	1 3/8	1 1/8	.906	
PA41	4/0 Str. AWG	2/0	1 3/8	1 1/8	.906	BROWN
PA25	250 kcmil	3/0	1 1/2	2 1/16	1.155	
PA30	300 kcmil	4/0	1 5/8	2 1/16	1.155	
PA35	350 kcmil	4/0	1 5/8	2 1/16	1.155	PINK
PA40	400 kcmil	250 kcmil	1 5/8	2 3/32	1.375	
PA50	500 kcmil	350 kcmil	1 5/8	2 3/32	1.375	YELLOW
PA60	600 kcmil	350 kcmil	1 5/8	2 3/4	1.500	
PA75	750 kcmil	500 kcmil	2	2 3/4	1.500	