



SAFETY DATA SHEET

1. Identification

Product identifier Spray Adhesive

Other means of identification

Product code 03018

Recommended use General purpose aerosol adhesive

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.
Warminster, PA 18974 US

Telephone

General Information 215-674-4300

Technical Assistance 800-521-3168

Customer Service 800-272-4620

24-Hour Emergency (CHEMTREC) 800-424-9300 (US)
703-527-3887 (International)

Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1
Gases under pressure Liquefied gas

Health hazards Skin corrosion/irritation Category 2
Serious eye damage/eye irritation Category 2A
Specific target organ toxicity, single exposure Category 3 narcotic effects
Aspiration hazard Category 1

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 2
Hazardous to the aquatic environment, long-term hazard Category 2

OSHA defined hazards Not classified.

Label elements



Signal word

Danger

Hazard statement

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Precautionary statement

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container: Do not pierce or burn, even after use. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Avoid breathing gas. Wash thoroughly after handling. Wear protective gloves and eye/face protection. Avoid release to the environment.

Response	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Collect spillage.
Storage	Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.
Disposal	Dispose of contents/container in accordance with local/regional/national regulations.
Hazard(s) not otherwise classified (HNOC)	None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
2-Methylpentane		107-83-5	10 - 20
Acetone		67-64-1	10 - 20
Cyclohexane		110-82-7	10 - 20
Dimethyl ether		115-10-6	10 - 20
1,1-Difluoroethane		75-37-6	5 - 10
2,2-Dimethylbutane		75-83-2	5 - 10
2,3-Dimethylbutane		79-29-8	5 - 10
3-Methylpentane		96-14-0	5 - 10
n-Butane		106-97-8	5 - 10
Propane		74-98-6	5 - 10

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. If breathing is difficult, trained personnel should give oxygen. Get medical attention immediately.
Skin contact	Remove contaminated clothing. Wash off with soap and plenty of water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. Aspiration may cause pulmonary edema and pneumonitis. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Diarrhea. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Alcohol resistant foam. Water. Dry powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire-fighting equipment/instructions

In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. Use standard firefighting procedures and consider the hazards of other involved materials. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.

General fire hazards

Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Avoid breathing gas. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. This product is miscible in water. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS. Prevent entry into waterways, sewer, basements or confined areas.

Environmental precautions

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

7. Handling and storage**Precautions for safe handling**

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing mist or vapor. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, please see the product label.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Secure cylinders in an upright position at all times, close all valves when not in use. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits****US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
Acetone (CAS 67-64-1)	PEL	2400 mg/m3 1000 ppm
Cyclohexane (CAS 110-82-7)	PEL	1050 mg/m3
Propane (CAS 74-98-6)	PEL	300 ppm 1800 mg/m3 1000 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
2,2-Dimethylbutane (CAS 75-83-2)	STEL	1000 ppm
	TWA	500 ppm
2,3-Dimethylbutane (CAS 79-29-8)	STEL	1000 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value
2-Methylpentane (CAS 107-83-5)	TWA	500 ppm
	STEL	1000 ppm
3-Methylpentane (CAS 96-14-0)	TWA	500 ppm
	STEL	1000 ppm
Acetone (CAS 67-64-1)	TWA	500 ppm
	STEL	750 ppm
Cyclohexane (CAS 110-82-7)	TWA	500 ppm
	TWA	100 ppm
n-Butane (CAS 106-97-8)	STEL	1000 ppm

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
2,2-Dimethylbutane (CAS 75-83-2)	Ceiling	1800 mg/m3
	TWA	510 ppm
		350 mg/m3
2,3-Dimethylbutane (CAS 79-29-8)	Ceiling	1800 mg/m3
	TWA	510 ppm
		350 mg/m3
2-Methylpentane (CAS 107-83-5)	Ceiling	1800 mg/m3
	TWA	510 ppm
		350 mg/m3
3-Methylpentane (CAS 96-14-0)	Ceiling	1800 mg/m3
	TWA	510 ppm
		350 mg/m3
Acetone (CAS 67-64-1)	TWA	100 ppm
		590 mg/m3
	TWA	250 ppm
Cyclohexane (CAS 110-82-7)	TWA	1050 mg/m3
		300 ppm
	TWA	1900 mg/m3
n-Butane (CAS 106-97-8)	TWA	800 ppm
		1800 mg/m3
	TWA	1000 ppm
Propane (CAS 74-98-6)	TWA	1800 mg/m3
		1000 ppm

US. AIHA Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
1,1-Difluoroethane (CAS 75-37-6)	TWA	2700 mg/m3
Dimethyl ether (CAS 115-10-6)	TWA	1000 ppm
		1880 mg/m3
	TWA	1000 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	50 mg/l	Acetone	Urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.
Individual protection measures, such as personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear protective gloves such as: Nitrile. Rubber.
Other	Wear appropriate chemical resistant clothing.
Respiratory protection	If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid.
Form	Aerosol.
Color	White.
Odor	Mint
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	-261.2 °F (-162.9 °C) estimated
Initial boiling point and boiling range	121.5 °F (49.7 °C) estimated
Flash point	67.2 °F (19.6 °C) Closed Cup
Evaporation rate	Moderate
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	1.2 % estimated
Flammability limit - upper (%)	8.4 % estimated
Vapor pressure	1874.8 hPa estimated
Vapor density	> 1 (air = 1)
Relative density	0.76
Solubility (water)	Negligible
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	473 °F (245 °C) estimated
Decomposition temperature	Not available.
Viscosity (kinematic)	Not available.
Percent volatile	82.8 %

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.

Conditions to avoid	Heat, flames and sparks. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Nitrates. Fluorine. Chlorine. Acids. Alkalies. Alkaline earth metals. Amines. Reducing agents.
Hazardous decomposition products	Hydrofluoric acid. Carbonyl fluoride. Carbon oxides. Hydrocarbons. Sulfur oxides.

11. Toxicological information

Information on likely routes of exposure

Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.
Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness and dizziness. Headache. Nausea, vomiting. Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Narcotic effects.

Product	Species	Test Results
Spray Adhesive		
Acute		
<i>Dermal</i>		
LD50	Rabbit	49998.5859 mg/kg estimated
<i>Inhalation</i>		
LC50	Rat	17429.1934 ppm, 4 hours estimated 10528 mg/l, 4 hours estimated
<i>Oral</i>		
LD50	Rat	32342.3555 mg/kg estimated

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation	Causes skin irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory sensitization	Not available.
Skin sensitization	This product is not expected to cause skin sensitization.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.
Specific target organ toxicity - repeated exposure	Not classified.
Aspiration hazard	May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death.
Chronic effects	Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Product	Species	Test Results
Spray Adhesive		
Aquatic		
Crustacea	EC50 Daphnia	33661.7773 mg/l, 48 hours estimated

Product	Species	Test Results
Fish	LC50	Fish 10012.3672 mg/l, 96 hours estimated
Components	Species	Test Results
Acetone (CAS 67-64-1)		
Aquatic		
Crustacea	EC50	Water flea (Daphnia magna) 21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 4740 - 6330 mg/l, 96 hours
Cyclohexane (CAS 110-82-7)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas) 23.03 - 42.07 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

1,1-Difluoroethane	0.75
2,2-Dimethylbutane	3.82
2,3-Dimethylbutane	3.42
2-Methylpentane	3.74
3-Methylpentane	3.6
Acetone	-0.24
Cyclohexane	3.44
Dimethyl ether	0.1
n-Butane	2.89
Propane	2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal of waste from residues / unused products If discarded, this product is considered a RCRA ignitable waste, D001. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity

Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed.
Cargo aircraft only	Allowed.

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS, LIMITED QUANTITY, MARINE POLLUTANT
Transport hazard class(es)	
Class	2
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	Yes
EmS	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

SARA 304 Emergency release notification

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Cyclohexane (CAS 110-82-7)

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)

Cyclohexane (CAS 110-82-7)

CERCLA Hazardous Substances: Reportable quantity

Acetone (CAS 67-64-1) 5000 LBS

Cyclohexane (CAS 110-82-7) 1000 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

1,1-Difluoroethane (CAS 75-37-6)

Dimethyl ether (CAS 115-10-6)

n-Butane (CAS 106-97-8)

Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1)

6532

Food and Drug Administration (FDA) Not regulated.**Superfund Amendments and Reauthorization Act of 1986 (SARA)****Section 311/312 Hazard categories** Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - Yes
Reactivity Hazard - No**SARA 302 Extremely hazardous substance** No**US state regulations****US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

US. New Jersey Worker and Community Right-to-Know Act2,2-Dimethylbutane (CAS 75-83-2)
2,3-Dimethylbutane (CAS 79-29-8)
2-Methylpentane (CAS 107-83-5)
Acetone (CAS 67-64-1)
1,1-Difluoroethane (CAS 75-37-6)
Cyclohexane (CAS 110-82-7)
Dimethyl ether (CAS 115-10-6)
n-Butane (CAS 106-97-8)
Propane (CAS 74-98-6)**US. Massachusetts RTK - Substance List**1,1-Difluoroethane (CAS 75-37-6)
2,2-Dimethylbutane (CAS 75-83-2)
2,3-Dimethylbutane (CAS 79-29-8)
2-Methylpentane (CAS 107-83-5)
3-Methylpentane (CAS 96-14-0)
Acetone (CAS 67-64-1)
Cyclohexane (CAS 110-82-7)
Dimethyl ether (CAS 115-10-6)
n-Butane (CAS 106-97-8)
Propane (CAS 74-98-6)**US. Pennsylvania Worker and Community Right-to-Know Law**Acetone (CAS 67-64-1)
Cyclohexane (CAS 110-82-7)
2,2-Dimethylbutane (CAS 75-83-2)
2,3-Dimethylbutane (CAS 79-29-8)
2-Methylpentane (CAS 107-83-5)
3-Methylpentane (CAS 96-14-0)
Dimethyl ether (CAS 115-10-6)
n-Butane (CAS 106-97-8)
Propane (CAS 74-98-6)**US. Rhode Island RTK**1,1-Difluoroethane (CAS 75-37-6)
Acetone (CAS 67-64-1)
Cyclohexane (CAS 110-82-7)
Dimethyl ether (CAS 115-10-6)
n-Butane (CAS 106-97-8)
Propane (CAS 74-98-6)**US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Benzene (CAS 71-43-2)	Listed: February 27, 1987
Ethanal (CAS 75-07-0)	Listed: April 1, 1988
Formaldehyde (CAS 50-00-0)	Listed: January 1, 1988

US - California Proposition 65 - CRT: Listed date/Developmental toxin

Benzene (CAS 71-43-2)

Listed: December 26, 1997

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

Benzene (CAS 71-43-2)

Listed: December 26, 1997

Volatile organic compounds (VOC) regulations**EPA****VOC content (40 CFR 51.100(s))** 63.8 %**Consumer products (40 CFR 59, Subpt. C)** Not regulated**State****Consumer products** This product is regulated as a Mist Spray Adhesive. This product is compliant for use in all 50 states.**VOC content (CA)** 63.8 %**VOC content (OTC)** 63.8 %**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	08-25-2014
Prepared by	Allison Cho
Version #	01
Further information	Not available.
HMIS® ratings	Health: 2 Flammability: 4 Physical hazard: 1 Personal protection: B
NFPA ratings	Health: 2 Flammability: 4 Instability: 1

NFPA ratings

Disclaimer

CRC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.