



## DWTT.E142707 Conduit Fittings

[Page Bottom](#)

### Conduit Fittings

[See General Information for Conduit Fittings](#)

#### L H DOTTIE CO

6131 GARFIELD AVE  
COMMERCE, CA 90040-3610 USA

E142707

**Bushings** Model(s) R364, R365, R366

**Conduit Nipples** Model(s) C-1210

**Connectors, flexible conduits** Model(s) SSQ90-100, SSQ90-125, SSQ90-150, SSQ90-200, SSQ90-250, SSQ90-300, SSQ90-350, SSQ90-38, SSQ90-400, SSQ90-50, SSQ90-75

**Connectors, flexible metal conduits** Model(s) SSQ-100, SSQ-125, SSQ-150, SSQ-200, SSQ-250, SSQ-300, SSQ-350, SSQ-38, SSQ-400, SSQ-50, SSQ-75

**Connectors, for liquid-tight flexible metal conduits, type 2** Model(s) SL100I, SL125I, SL150I, SL200I, SL250I, SL300I, SL350I, SL400I, SL45100, SL45100I, SL45125, SL45150, SL45150I, SL45200, SL45250I, SL45300I, SL45400I, SL4550, SL4550I, SL4575, SL4575I, SL50I, SL75I, SL90100, SL90100I, SL90125, SL90125I, SL90150, SL90150I, SL90200, SL90250I, SL90300I, SL90350I, SL9038, SL90400I, SL9050, SL9050I, SL9075, SL9075I

**Connectors, for rigid metal conduits** Model(s) NT200, NT200I, NT250I, NT350I

**Connectors, for rigid metal or IMC conduits** Model(s) NT100, NT100I, NT125, NT125I, NT150, NT150I, NT300I, NT400I, NT50, NT50I, NT75, NT75I

**Connectors, liquid-tight flexible metal conduits** Model(s) LH-LTA350I, LH-LTA400I, LT 037, LT 037 I, LT 050, LT 050 I, LT 075, LT 075 I, LT 100, LT 100 I, LT 125, LT 125 I, LT 150, LT 150 I, LT 200, LT 200 I, LT 250, LT 250 I, LT 300, LT 300 I, LT 350, LT 350 I, LT 400, LT 400 I, LT90-037, LT90-037 I, LT90-050, LT90-050 I, LT90-075, LT90-075 I, LT90-100, LT90-100 I, LT90-125, LT90-125 I, LT90-150, LT90-150 I, LT90-200, LT90-200 I, LT90-250 I, LT90-300 I, LT90-350 I, LT90-400 I

**Connectors, liquid-tight, flexible metal conduits, type 2** Model(s) SL100, SL10045, SL10045I, SL10090, SL10090I, SL100I, SL125, SL12545, SL12545I, SL12590, SL12590I, SL125I, SL150, SL15045, SL15045I, SL15090, SL15090I, SL150I, SL200, SL20045, SL20045I, SL20090, SL20090I, SL200I, SL38, SL3845, SL3845I, SL3890, SL3890I, SL38I, SL50, SL5045, SL5045I, SL5090, SL5090I, SL50I, SL75, SL7545, SL7545I, SL7590, SL7590I, SL75I

**Connectors, metallic and nonmetallic, liquid-tight flexible conduit** Model(s) LT-100, LT-100-I, LT-125, LT-125-I, LT-150, LT-150-I, LT-200, LT-200-I, LT-250, LT-300, LT-350, LT-38, LT-38-I, LT-400, LT-50, LT-50-I, LT-75, LT-75-I, LT90-100, LT90-100-I, LT90-125, LT90-125-I, LT90-150-I, LT90-200, LT90-200-I, LT90-250, LT90-300, LT90-350, LT90-38, LT90-38-I, LT90-400, LT90-50, LT90-50-I, LT90-75, LT90-75-I

**Couplings, for rigid metal conduit** Model(s) NTC200, NTC250, NTC300, NTC400

**Couplings, liquid tight** Model(s) CF1, CF2, CF3

**Couplings, liquid-tight, for rigid metal conduit or IMC to IMC** Model(s) NTC100, NTC125, NTC150, NTC50, NTC75

**Elbows** Model(s) PE1, PE1G, PE2, PE2G, PE3, PE3G

**Hubs, for use with threaded rigid conduits** Model(s) WTH-100, WTH-125, WTH-150, WTH-200, WTH-250, WTH-300, WTH-350, WTH-400, WTH-50, WTH-75

**Nipples** Model(s) CN-100, CN-125, CN-150, CN-200, CN-250, CN-300, CN-350, CN-400, CN-50, CN-75, ON-100, ON-125, ON-150, ON-200, ON-50, ON-75

**Nipples, offset** Model(s) ON-050, ON-075, ON-250, ON-300

**Reducing Bushings** Model(s) R352, R353, R354, R355, R356, R357, R358, R359, R360, R361, R362, R363, R364, R365, R366, R367, R368, R369, R370, R371, R372, R373, R374, R375, R376

**Sealing locknuts** Model(s) LNS100, LNS125, LNS150, LNS200, LNS50, LNS75

NOTE - Provided with or without suffix B, GT or M

[Last Updated](#) on 2017-10-06

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".