

TYPE
SS
SSK
SSKC

Features

- Watertight EPDM rubber splice cover
- Tapered ends
- Ready for installation
- Type SS is cover only supplied with lubricant
- Type SSK kit is supplied with both connector and lubricant

Benefits

- No taping required. Suitable for direct burial
- Fits a wide range of conductor sizes
- Not a mold, can be used in any type of weather. (moisture and humidity are not a factor)
- Can be used with standard aluminum or copper compression from 500kcmil - 6. Lubricant permits easy insertion of conductors into sleeve.
- Supplied with dual-rated mechanical splice connector with a wire range of 350kcmil - 6



Fig. 1



Fig. 2

Catalog Number	Figure Number	Wire Range		L
		Bolted Connector	Compression Sleeves	
SSK-350-Z	1	350kcmil-6	-	5-1/2
SS-350-Z	2	350kcmil-6	500kcmil-6	5-1/2



Catalog Number	Connector Catalog Number	Wire Size	Wire Range When Installed With IDT-12 Tool
SSKC-6-Z	AS-6	6	6
SSKC-4-Z	AS-4	4	4-6
SSKC-2-Z	AS-2	2	2-6
SSKC-1/0-Z	AS-1/0	1/0	1/0-1
SSKC-2/0-Z	AS-2/0	2/0	2/0-1
SSKC-3/0-Z	AS-3/0	3/0	3/0-1
SSKC-4/0-Z	AS-4/0	4/0	4/0-1
SSKC-250-Z	AS-250	250kcmil	250kcmil-1/0

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

TYPE
SS
SSK
SSKC

Features

- Watertight EPDM rubber splice cover
- Tapered ends
- Ready for installation
- Type SS is cover only supplied with lubricant
- Type SSK kit is supplied with both connector and lubricant
- Connector rated for 600 volts, 90° C

Benefits

- No taping required. Suitable for direct burial
- Fits a wide range of conductor sizes
- Not a mold, can be used in any type of weather. (moisture and humidity are not a factor)
- Can be used with standard aluminum or copper compression from 500kcmil - 6. Lubricant permits easy insertion of conductors into sleeve.
- Supplied with dual-rated mechanical splice connector with a wire range of 350kcmil - 6
- Ensures reliability



Fig. 1



Fig. 2

Catalog Number	Figure Number	Wire Range		L
		Bolted Connector	Compression Sleeves	
SSK-350-Z	1	350kcmil-6	-	5-1/2
SS-350-Z	2	350kcmil-6	500kcmil-6	5-1/2



Catalog Number	Connector Catalog Number	Wire Size	Wire Range When Installed With IDT-12 Tool
SSKC-6-Z	AS-6	6	6
SSKC-4-Z	AS-4	4	4-6
SSKC-2-Z	AS-2	2	2-6
SSKC-1/0-Z	AS-1/0	1/0	1/0-1
SSKC-2/0-Z	AS-2/0	2/0	2/0-1
SSKC-3/0-Z	AS-3/0	3/0	3/0-1
SSKC-4/0-Z	AS-4/0	4/0	4/0-1
SSKC-250-Z	AS-250	250kcmil	250kcmil-1/0

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)