



...



LED PAR38

# 13PAR38/LED/940/F 6/1FB

**Order code:** 567776[Sales Office Locator](#)

## Specifications

### General Information

Base	E26 [ Single Contact Medium Screw]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	25000 h
Switching Cycle	25000X

### Light Technical

Color Code	940 [ CCT of 4000K]
Beam Angle (Nom)	25 °
Initial lumen (Nom)	1200 lm
Luminous Intensity (Nom)	6000 cd

[Clear all](#)**Add two products to start comparing**[Hide](#)

Correlated Color Temperature (Nom) 4000 K

[Compare now](#)[Add product](#)

Color Consistency

[Add product](#)[Add product](#) <4

Color Rendering Index (Nom) 90

LLMF At End Of Nominal Lifetime (Nom) 70 %

### Operating and Electrical

Input Frequency 50 to 60 Hz

Power (Rated) (Nom) 13 W

Lamp Current (Nom) 120 mA

Wattage Equivalent 120 W

Starting Time (Nom) 0.5 s

Warm Up Time to 60% Light (Nom) 0.5 s

Power Factor (Nom) 0.9

Voltage (Nom) 120 V

### Temperature

T-Case Maximum (Nom) 75 °C

### Controls and Dimming

Dimmable Only with specific dimmers

### Mechanical and Housing

Bulb Shape PAR38 [ PAR 4.75 inch/121mm]

### Approval and Application

Suitable For Accent Lighting Yes

### Product Data

Order product name 13PAR38/LED/940/F25/DIM/GULW/T20