

Push Buttons

High Voltage

800 Series



The 850 and 854 Push Buttons are rugged, fast make and break contact push buttons that operate regardless of how pressure is applied or released. The buttons have insulated, protective sleeves and phosphor bronze, self cleaning contacts that withstand shock and vibration.

Both push buttons panel mount in a 7/8" (22mm) hole using the supplied locknut. Also mounts in a 7/8" (20mm) hole that has been tapped with straight pipe threads.

May be used with 149-1 mounting plate.

Features and Specifications

- Locknut mounting
- Convenient screw terminals
- Normally open contacts (**850**)
- Normally closed contacts (**854**)
- Momentary contacts
- 3" wire leads (**850**)
- UL registered (**850**)

Ordering Information

Description	Cat. No.	Operating Voltage	Current		Finish		Hole	
			DC	AC	Housing	Center	Size	Depth
Push Button Normally Open Contacts	850	12V AC	-	15 A	Heavy Duty- Chrome Plated	Black	7/8" (22mm)	1 3/4" (44mm)
		24V AC	-	15 A		Black	7/8" (22mm)	1 3/4" (44mm)
		48V AC	-	10 A		Black	7/8" (22mm)	1 3/4" (44mm)
		125V AC	-	5 A		Black	7/8" (22mm)	1 3/4" (44mm)
		250V AC	-	5 A		Black	7/8" (22mm)	1 3/4" (44mm)
Push Button Normally Closed Contacts	854	12V AC	4 A	4 A	Heavy Duty- Chrome Plated	Black	7/8" (22mm)	1 3/4" (44mm)
		24V AC	4 A	4 A		Black	7/8" (22mm)	1 3/4" (44mm)
		48V AC	2 A	4 A		Black	7/8" (22mm)	1 3/4" (44mm)
		125V AC	1 A	2 A		Black	7/8" (22mm)	1 3/4" (44mm)
		250V AC	0.5 A	1 A		Black	7/8" (22mm)	1 3/4" (44mm)

Accessories

Description	Cat. No.
Mounting Plate	149-1

Weights and Dimensions

Cat. No.	Approx. Net Weight (lb.)	Approx. Shipping Weight (lb.)
850	0.14	0.21
854	0.14	0.21
149-1	0.12	0.15

