

INCANDESCENT LIGHTING

Box & Wall Vaportite

VTB, VTW Series

SPECIFICATIONS

- cULus Listed for wet locations.

FEATURES

- For well or pit lighting, indicators on docks, industrial and commercial lighting.
- Heavy duty die cast aluminum housing.
- One piece locking die cast aluminum guard with grey polyester powder coat finish.
- Screw in tempered glass globe.
- 1/2" NPT knockouts.
- Lamp not included.



CAT. NO.	FIG. NO.	DESCRIPTION	HEIGHT (L) (IN.)	WIDTH (W) (IN.)	LAMP	STD. CTN. QTY.
VTB15012	1	Box 150 Watt 1/2" Vaportite	9	4.125	Incandescent	—
VTW15012	2	Wall 150 Watt 1/2" Vaportite	10	7.13	Incandescent	—
CG150	3	Clear Glass Globe for 150 Series Vaportite Fixtures	—	—	—	—

ACCESSORIES

SLUL, SC, RS Series



CAT. NO.	FIG. NO.	DESCRIPTION	HEIGHT (L) (IN.)	WIDTH (W) (IN.)	LAMP	STD. CTN. QTY.
SLUL100 (UL Listed)	1	100 Ft. With Molded Sockets In 10 Ft. Intervals. 150 Watts. Osha And Nec Compliant. High Visibility Yellow	—	—	—	1
SC200	2	Standard Cage	—	—	—	24
RS200	3	Rotatable Socket 200 Watt	—	—	—	24