

# CABLE TIES Releasable & Stainless Steel Ties -R, SS SERIES



## RELEASABLE




- Releasable ties are manufactured from either natural Nylon 66 or Weather Resistant Nylon 66, these ties can be easily released and re-used.

### TEMPERATURE RATING:

-40 °C to 85 °C (-40 °F to 185 °F).

MAX. WIRE/CABLE SIZE	CAT. NO.	MAX. BUNDLE DIA.	MIN. TENSILE STRENGTH	LENGTH (IN.)	WIDTH (IN.)	STD. PKG. QTY.	STD. CTN. QTY.
8"	<b>850-R</b>	2.000	50 Lbs.	8.00	0.210	100	1,000

## STAINLESS STEEL CABLE TIES



- Made of Grade 304 stainless steel and are ideally suited for hazardous environments.
- Roller-ball design that is self locking, fast and easy to install.
- Smooth edges will not damage wires.
- Installation by hand or with a tool.
- Available with a non-toxic, halogen-free polyester coating in a wide choice of colors.
- Available in Grade 316, for applications that require extremely high corrosion resistance. To order 316SS material, add suffix "-316" to part number.

### TEMPERATURE RATING:

-80 °C to 538 °C (-62.2 °F to 281.1 °F).

### TRUE PLENUM RATING

Air handling ties approved for indoor use in air handling spaces and plenums and ducts per NFPA-1993.

MAX. WIRE/CABLE SIZE	CAT. NO.	MAX. BUNDLE DIA.	MIN. TENSILE STRENGTH	LENGTH (IN.)	WIDTH (IN.)	STD. PKG. QTY.	STD. CTN. QTY.
8"	<b>SS8100</b>	1.970	100 Lbs.	8.000	0.181	100	500
14"	<b>SS14100</b>	3.940	100 Lbs.	14.000	0.181	100	500
	<b>SS14250</b>	3.940	250 Lbs.	14.000	0.311	100	500
20"	<b>SS20100</b>	5.900	100 Lbs.	20.5	0.181	100	500
	<b>SS20250</b>	5.900	250 Lbs.	20.5	0.311	100	500
26"	<b>SS26250</b>	7.870	250 Lbs.	26.5	0.311	100	500