

Kellems® Wire Management Products  
**Metallic Liquidtight Conduit Fittings**



**Straight Conduit Fitting**

| Trade Size (metric designator) | Insulated | Non-Insulated |
|--------------------------------|-----------|---------------|
| 3/8 (9)                        | H0381     | H038          |
| 1/2 (13)                       | H0501     | H050          |
| 3/4 (19)                       | H0751     | H075          |
| 1 (25)                         | H1001     | H100          |
| 1 1/4 (32)                     | H1251     | H125          |
| 1 1/2 (38)                     | H1501     | H150          |
| 2 (51)                         | H2001     | H200          |
| 2 1/2 (63)                     | H2501     | H250          |
| 3 (76)                         | H3001     | H300          |
| 3 1/2 (89)                     | H3501     | H350          |
| 4 (102)                        | H4001     | H400          |

Note: See page T-116 for additional technical data.



**Straight with Male  
Hubbell Conduit Fitting  
H050**

**45° Conduit Fitting**

| Trade Size (metric designator) | Insulated | Non-Insulated |
|--------------------------------|-----------|---------------|
| 3/8 (9)                        | H03841    | H0384         |
| 1/2 (13)                       | H05041    | H0504         |
| 3/4 (19)                       | H07541    | H0754         |
| 1 (25)                         | H10041    | H1004         |
| 1 1/4 (32)                     | H12541    | H1254         |
| 1 1/2 (38)                     | H15041    | H1504         |
| 2 (51)                         | H20041    | H2004         |

Note: See page T-116 for additional technical data.



**45° Angle with Male  
Hubbell Conduit Fitting  
H0504**

**90° Conduit Fitting**

| Trade Size (metric designator) | Insulated | Non-Insulated |
|--------------------------------|-----------|---------------|
| 3/8 (9)                        | H03891    | H0389         |
| 1/2 (13)                       | H05091    | H0509         |
| 3/4 (19)                       | H07591    | H0759         |
| 1 (25)                         | H10091    | H1009         |
| 1 1/4 (32)                     | H12591    | H1259         |
| 1 1/2 (38)                     | H15091    | H1509         |
| 2 (51)                         | H20091    | H2009         |
| 2 1/2 (63)                     | H25091    | H2509         |
| 3 (76)                         | H30091    | H3009         |
| 4 (102)                        | H40091    | H4009         |

Notes: 3/8" Liquidtight conduit fitting have 1/2 N.P.T. male threads.  
 For use with Liquidtight Metal conduit and PolyTuff I Non-Metallic conduit.  
 See page T-116 for additional technical data.



**90° Angle with Male  
Hubbell Conduit Fitting  
H0509**