



Liquidtight Flexible Cord & Cable Fittings

T&B Catalog Number:

4961

UPC Number:

78621004961

Status:

Active

Description:

1/2 in. 90 degree malleable iron Ranger liquidtight cord connector, cord range .310-.560

Features

Extended range with superior strain relief.

Reduced overall size, fits into tighter spaces.

Gland nut designed to restrict cable bending.

Application

Provide a means for passing a cord cable into an enclosure through a bulkhead

Suitable for Ordinary, Wet or Dry locations.

Suitable for use in hazardous locations where general purpose equipment is specifically permitted by NEC 501-4(b).

General

Material Malleable Iron

Cord and Cable Types S, SO, SV, ST, STD, SJ, SJO, SJT, SJTO, SVD

Dimension Information

Hub Size (inches) 1/2

Dimension A (inches) 1 1/8

Dimension B (inches) 1 3/4

Dimension C (inches) 5/8

Cord Range (inches) .310-.560

Throat Diameter (inches) 19/32

Specifications

3dmodel Available on Website

Packaging

T&B Inner Pack 25

Package in Units 50

T&B Sold in UOM Each

T&B Weight Per UOM 23 lbs. per 100

Application Support

Product Overview Available on Website

Specifications Available on Website

Portable Cord Selection Table Available on Website

Notes

Suitable for use in hazardous locations where general purpose equipment is specifically permitted by NEC 501-4(b).

Certifications

RoHS Compliance Yes

Certifications



File Nbr:
E 13938

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com