



## Dual Range Non-Contact Voltage Tester 12 - 1000V AC

NCVT2P



- Dual ranges indicates low voltage (12 to 48V AC) and standard voltage (70 to 1000V AC) allowing broad application
- Detects 12 to 1000V AC with simultaneous visual and audible voltage indicators
- Non-contact detection of low voltage in security, entertainment, communications, environmental control, and irrigation systems
- Green light indicates no voltage
- Lightweight, compact tool with pocket clip provides convenient storage and quick access
- Auto power-off feature conserves and extends battery life
- CAT IV 1000 V rating provides expanded operation and protection
- Screw-thread battery cap with O-ring ensures protection against dust and water ingress
- 6.6-Foot (2 m) drop protection
- IP67: Dustproof and waterproof
- Conforms to CE requirements
- US Patent 10,073,142, D750,985 and other patents pending



The NCVT-2P is a non-contact voltage tester that detects 12 to 1000V AC and indicates the presence of voltage in cables, cords, circuit breakers, light fixtures, switches, outlets and wires as well as AC voltage in doorbells, thermostats, low voltage lighting and irrigation systems. Includes both visual and audible signals. The NCVT-2P is rugged enough for any job site.

### Specifications

Type:	Dual Range	Standard:	CAT IV 1000V
Application:	Non-Contact Detection and Testing of AC Voltage	Included:	Batteries
Special Features:	Two Distinctive Modes: 70 to 1000V AC and 12 to 1000V AC	Batteries:	2 x AAA
Material:	Polycarbonate	Battery Life:	142 Hrs
Drop Protection:	6.6' (2 m)	Overall Length:	5.82" (14.8 cm)
Voltage:	12 - 1000V AC	Overall Height:	1.09" (2.8 cm)
Frequency:	50 - 500 Hz	Overall Width:	0.86" (2.2cm)
Pollution Degree:	2	Weight:	1.7 oz (48.1 g)
Ingress Protection:	IP54	UPC:	092644692321



[Privacy Policy](#) [Terms & Conditions](#) [Contact Us](#)

© 2020 Klein Tools, Inc. • All Rights Reserved