

5" Vertical Compact Fluorescent


Non-IC Rated Full Reflectors – All reflectors are damp location listed. Lamp types and maximum wattages are listed for each reflector. Maximum ceiling thickness 1/2". Consult factory for thicker ceiling applications.

LQJ

COMPACT FLUORESCENT DOWNLIGHTS


Open reflector

J01 White
Other finishes: AZ/GZ




Open cone

JC1
Other finishes: AZ/GZ/BLZ




Premium metal baffle

JB1 White reflector/
black baffle
Other finishes: W



Baffle

JB4 White reflector/
black baffle
Other finishes: W/C/G



1-Lamp, Double Twin-Tube (DTT)



Intended Use

New construction applications requiring high performance vertical reflectors using compact fluorescent lamps.

Features

Mechanical – Rugged, galvanized steel frame-in with trim retaining clips to secure optical system. Galvanized bar hangers span up to 24" o.c. and feature built-in nailers and T-bar clips. Galvanized steel junction box with removable access door, (4) Romex knockouts, (2) 3/4" and (4) 1/2" nominal conduit knockouts with pryout slots.

Electrical System – Normal power factor (NPF) ballast standard. Electronic multi-volt ballast, 120V through 277V with end of life protection. Maximum 8 (4 in, 4 out) No. 12 AWG conductor. Rated for 90°C supply wire. Ground wire provided. Class P thermally protected ballast protects against improper contact with insulation and approved for through-branch circuit wiring.

Listings

UL Listed to U.S. and Canadian safety standards.

Ordering Information

Example: LQJ 13DTT J01 120

Series	Wattage/lamp	Reflector	Voltage	Options
LQJ	13DTT	J01 White open reflector	120	GEB10 Generic electronic ballast, THD (total harmonic distortion) <10%.
		J01AZ Clear specular open reflector	277	HPF High power factor (90% power factor).
		J01GZ Gold specular open reflector	347	GMF Single slow-blow fuse.
		JC1AZ Clear specular cone		LRC Provides compatibility with Lithonia Reloc System.
		JC1GZ Gold specular cone		WLP 35K lamp (shipped separately).
		JC1BLZ Black specular cone		
		JB1 White reflector/black baffle		
		JB1W White reflector/white baffle		
		JB4 White reflector/black baffle		
		JB4W White reflector/white baffle		
		JB4C White reflector/chrome baffle		
		JB4G White reflector/gold baffle		

Drawings are for dimensional detail only and may not represent actual mechanical configuration. Dimensions are shown in inches.

STANDARD PACKAGING
To order, use single master catalog number.
Example: (13) LQJ 13DTT J01 120
Fixtures ship as multiple components using optimized packaging. Example above ships as:
(Qty 13) LQJ 13DTT 120 (13 cartons of 1 housing)
(Qty 13) J01 (13 cartons of 1 reflector)

