



Cable Clamps



Features

- Use to secure wires, cables, pipes, tubing, fiber optics
- Ultraviolet black nylon clamps available for internal and external use
- Use with #10 screw

Models

Desc.	Closed Diameter	Center to Center	Width	Thickness	Mounting Hole	Qty./ Bag	Cat. No.
Natural Nylon	.125 in./3.18mm	.343 in./ 8.71mm	3/8 in.	.050 in./ 1.27mm	.203 in./ 5.16mm	100	IT125CCL-C
Natural Nylon	.250 in./ 6.35mm	.421 in./ 10.69mm	3/8 in.	.050 in./ 1.27mm	.203 in./ 5.16mm	100	IT250CCL-C
UV Black Nylon	.250 in./ 6.35mm	.421 in./ 10.69mm	3/8 in.	.050 in./ 1.27mm	.203 in./ 5.16mm	100	IT250CCL-C0
Natural Nylon	.375 in./ 9.52mm	.500 in./ 12.70mm	1/2 in.	.060 in./ 1.52mm	.203 in./ 5.16mm	100	IT375CCL2-C
UV Black Nylon	.375 in./ 9.52mm	.500 in./ 12.70mm	1/2 in.	.060 in./ 1.52mm	.203 in./ 5.16mm	100	IT375CCL2-C0
Natural Nylon	.500 in./12.70mm	.553 in./ 14.05mm	1/2 in.	.060 in./ 1.52mm	.203 in./ 5.16mm	100	IT500CCL2-C
Natural Nylon	.625 in./15.88mm	.625 in./ 15.88mm	1/2 in.	.060 in./ 1.52mm	.203 in./ 5.16mm	100	IT625CCL2-C
Natural Nylon	Natural/19.05mm	.699 in./ 17.75mm	1/2 in.	.060 in./ 1.52mm	.203 in./ 5.16mm	100	IT750CCL2-C
Natural Nylon	1.000 in./ 25.40mm	.825 in./ 20.96mm	1/2 in.	.060 in./ 1.52mm	.203 in./ 5.16mm	100	IT1000CCL2-C

©2011 IDEAL INDUSTRIES, INC. All rights reserved.