

# ProLume. Bare Spirals - Quick Reference Guide

Bulb Type	Base	Product #	Product Code	Description	Pkg Qty	Color Temp	CRI	Initial Lumens	Incandescent Equivalent	Life	MOL (Inc)	MOD (Inc)
<b>5 Watts</b>												
T2	Cand.	✓ 45011	*CFL5/27/E12	Warm White	10/50	2700	82	250	25	10000	3.50"	1.38"
T2	Cand.	45015	*CFL5/35/E12	White	10/50	3500	82	250	25	10000	3.50"	1.38"
T2	Cand.	45017	*CFL5/41/E12	Cool White	10/50	4100	82	250	25	10000	3.50"	1.38"
T2	Cand.	45019	*CFL5/50/E12	Natural White	10/50	5000	82	250	25	10000	3.50"	1.38"
T2	Med.	✓ 45010	*CFL5/27	Warm White	10/50	2700	82	250	25	10000	3.56"	1.38"
T2	Med.	46600	CFL5/27/FS	Warm White Full Spiral	10/50	2700	82	300	25	12000	2.98"	1.93"
T2	Med.	45014	*CFL5/35	White	10/50	3500	82	250	25	10000	3.56"	1.38"
T2	Med.	45016	*CFL5/41	Cool White	10/50	4100	82	250	25	10000	3.56"	1.38"
T2	Med.	45018	*CFL5/50	Natural White	10/50	5000	82	250	25	10000	3.56"	1.38"
<b>9 Watts</b>												
T2	Cand.	✓ 45031	*CFL9/27/E12	Warm White	10/50	2700	82	500	40	10000	4.00"	1.57"
T2	Cand.	45035	*CFL9/35/E12	White	10/50	3500	82	500	40	10000	4.00"	1.57"
T2	Cand.	✓ 45037	*CFL9/41/E12	Cool White	10/50	4100	82	500	40	10000	4.00"	1.57"
T2	Cand.	45039	*CFL9/50/E12	Natural White	10/50	5000	82	500	40	10000	4.00"	1.57"
T2	Med.	✓ 45030	*CFL9/27	Warm White	10/50	2700	82	500	40	10000	4.06"	1.57"
T2	Med.	46605	CFL9/27/FS	Warm White Full Spiral	10/50	2700	82	500	40	12000	3.41"	1.93"
T2	Med.	✓ 45034	*CFL9/35	White	10/50	3500	82	500	40	10000	4.06"	1.57"
T2	Med.	✓ 45036	*CFL9/41	Cool White	10/50	4100	82	500	40	10000	4.06"	1.57"
T2	Med.	45038	*CFL9/50	Natural White	10/50	5000	82	500	40	10000	4.06"	1.57"
<b>11 Watts</b>												
T3	Med.	✓ 109240	CFL11/27	Warm White	10/50	2700	82	700	40	12000	4.29"	1.85"
T3	Med.	✓ 109242	CFL11/41	Cool White	10/50	4100	82	700	40	12000	4.29"	1.85"
T3	Med.	✓ 109244	CFL11/50	Natural White	10/50	5000	82	700	40	12000	4.29"	1.85"
T3	Med.	109224	CFL11/BLU	Blue	10/50	-	-	-	-	8000	4.29"	1.85"
T3	Med.	109226	CFL11/GRN	Green	10/50	-	-	-	-	8000	4.29"	1.85"
T3	Med.	109220	CFL11/RED	Red	10/50	-	-	-	-	8000	4.29"	1.85"
T3	Med.	109222	CFL11/YEL	Yellow	10/50	-	-	-	-	8000	4.29"	1.85"
<b>13 Watts</b>												
T2	Cand.	45052	*CFL13/27/T2/E12	Warm White	10/50	2700	82	900	60	12000	4.19"	1.81"
T2	Cand.	45055	*CFL13/35/T2/E12	White	10/50	3500	82	900	60	10000	4.19"	1.81"
T2	Cand.	✓ 45057	*CFL13/41/T2/E12	Cool White	10/50	4100	82	850	60	10000	4.19"	1.81"
T2	Cand.	45059	*CFL13/50/T2/E12	Natural White	10/50	5000	82	850	60	10000	4.19"	1.81"
T2	Med.	✓ 45049	*CFL13/27/T2	Warm White	10/50	2700	82	900	60	10000	4.19"	1.81"
T2	Med.	✓ 45071	*CFL13/27/T2/4PK	Warm White 4-Pack	20/60	2700	82	900	60	10000	4.19"	1.81"
T2	Med.	✓ 46610	CFL13/27/FS	Warm White Full Spiral	10/50	2700	82	840	60	12000	3.84"	1.93"
T2	Med.	45054	*CFL13/35/T2	White	10/50	3500	82	900	60	10000	4.19"	1.81"
T2	Med.	✓ 45056	*CFL13/41/T2	Cool White	10/50	4100	82	850	60	10000	4.19"	1.81"
T2	Med.	✓ 45073	*CFL13/41/T2/4PK	Cool White 4-Pack	20/60	4100	82	850	60	10000	4.19"	1.81"
T2	Med.	✓ 45058	*CFL13/50/T2	Natural White	10/50	5000	82	850	60	10000	4.19"	1.81"
T2	GU24	✓ 46506	*CFL13/27/GU24	Warm White GU24	10/50	2700	82	800	60	10000	3.63"	1.81"
T2	GU24	✓ 46525	*CFL13/35/GU24	White GU24	10/50	3500	82	800	60	10000	3.63"	1.81"
T2	GU24	✓ 46526	*CFL13/41/GU24	Cool White GU24	10/50	4100	82	800	60	10000	3.63"	1.81"
T2	GU24	46527	*CFL13/50/GU24	Natural White GU24	10/50	5000	82	800	60	10000	3.63"	1.81"
T3	Med.	✓ 45101	*CFL13/27	Warm White	10/50	2700	82	900	60	12000	4.41"	1.97"
T3	Med.	45103	*CFL13/35	White	10/50	3500	82	900	60	12000	4.41"	1.97"
T3	Med.	45104	*CFL13/41	Cool White	10/50	4100	82	900	60	12000	4.41"	1.97"
T3	Med.	45105	*CFL13/50	Natural White	10/50	5000	82	900	60	12000	4.41"	1.97"
T3	Med.	45107	*CFL13/65	Daylight	10/50	6500	82	850	60	12000	4.41"	1.97"
T3	GU24	✓ 46544	CFL13/27/GU24/DIM	Warm White Dimmable	10/50	2700	82	800	60	10000	4.00"	1.81"
<b>13/20/25 Watts</b>												
T3	Med.	✓ 45720	CFL25/27/3WAY	Warm White 3-Way	10/50	2700	82	900/1200/1600	30/70/100	8000	6.13"	2.36"
T3	Med.	45721	CFL25/41/3WAY	Cool White 3-Way	10/50	4100	82	900/1200/1600	30/70/100	8000	6.13"	2.36"
<b>15 Watts</b>												
T3	Med.	✓ 109252	CFL15/27	Warm White	10/50	2700	82	950	60	10000	4.94"	1.85"
T3	Med.	109330	CFL15/35	White	10/50	3500	82	950	60	10000	4.94"	1.85"
T3	Med.	109261	CFL15/41	Cool White	10/50	4100	82	950	60	10000	4.94"	1.85"
T3	Med.	109272	CFL15/50	Natural White	10/50	5000	82	950	60	10000	4.94"	1.85"
T3	Med.	109270	CFL15/BLB	Blacklight-Blue	1/20	-	-	-	60	12000	4.94"	1.85"
T3	Med.	109288	CFL15/YEL	Yellow	1/50	-	-	-	60	12000	4.94"	1.85"
T3	Med.	46330	CFL15/27/DIM	Warm White Dimmable	10/50	2700	82	900	60	10000	4.92"	1.81"
<b>18 Watts</b>												
T2	Med.	✓ 45062	*CFL18/27/T2	Warm White	10/50	2700	82	1100	75	10000	4.56"	2.13"
T2	Med.	✓ 46615	CFL18/27/FS	Warm White Full Spiral	10/50	2700	82	1100	75	12000	4.56"	2.13"
T2	Med.	45064	*CFL18/35/T2	White	10/50	3500	82	1100	75	10000	4.56"	2.13"
T2	Med.	45065	*CFL18/41/T2	Cool White	10/50	4100	82	1100	75	10000	4.56"	2.13"
T2	Med.	45066	*CFL18/50/T2	Natural White	10/50	5000	82	1100	75	10000	4.27"	2.17"
T2	GU24	✓ 46512	*CFL18/27/GU24	Warm White GU24	10/50	2700	82	1200	75	10000	3.90"	2.13"

# ProLume. Bare Spirals - Quick Reference Guide

Bulb Type	Base	Product #	Product Code	Description	Pkg Qty	Color Temp	CRI	Initial Lumens	Incandescent Equivalent	Life	MOL (Inc)	MOD (Inc)
<b>18 Watts continued</b>												
T2	GU24	46519	*CFL18/35/GU24	White GU24	10/50	3500	82	1200	75	10000	3.90"	2.13"
T2	GU24	✓ 46520	*CFL18/41/GU24	Cool White GU24	10/50	4100	82	1200	75	10000	3.90"	2.13"
T2	GU24	46521	*CFL18/50/GU24	Natural White GU24	10/50	5000	82	1200	75	10000	3.90"	2.13"
T3	Med.	45120	*CFL18/27	Warm White	10/50	2700	82	1200	75	12000	5.24"	2.05"
T3	Med.	45122	*CFL18/35	White	10/50	3500	82	1200	75	12000	5.24"	2.05"
T3	Med.	45123	*CFL18/41	Cool White	10/50	4100	82	1200	75	12000	5.24"	2.05"
T3	Med.	45124	*CFL18/50	Natural White	10/50	5000	82	1200	75	12000	5.24"	2.05"
T3	GU24	46546	CFL18/27/GU24/DIM	Warm White Dimmable	10/50	2700	82	1200	75	10000	4.40"	2.05"
<b>20 Watts</b>												
T3	Med.	✓ 109254	CFL20/27	Warm White	10/50	2700	82	1250	75	12000	5.25"	2.05"
T3	Med.	109263	CFL20/41	Cool White	10/50	4100	82	1250	75	12000	5.25"	2.05"
T3	Med.	109274	CFL20/50	Natural White	10/50	5000	82	1250	75	12000	5.25"	2.05"
<b>23 Watts</b>												
T2	Med.	✓ 45075	*CFL23/27/T2	Warm White	10/50	2700	82	1600	100	10000	4.92"	2.13"
T2	Med.	✓ 46620	CFL23/27/FS	Warm White Full Spiral	10/50	2700	82	1600	100	12000	4.65"	2.28"
T2	Med.	45077	*CFL23/41/T2	Cool White	10/50	4100	82	1600	100	10000	4.92"	2.13"
T2	Med.	45079	*CFL23/50/T2	Natural White	10/50	5000	82	1600	100	10000	4.92"	2.13"
T2	GU24	✓ 46518	*CFL23/27/GU24	Warm White GU24	10/50	2700	82	1600	100	10000	4.41"	2.13"
T2	GU24	46522	*CFL23/35/GU24	White GU24	10/50	3500	82	1600	100	10000	4.41"	2.13"
T2	GU24	✓ 46523	*CFL23/41/GU24	Cool White GU24	10/50	4100	82	1600	100	10000	4.41"	2.13"
T2	GU24	46524	*CFL23/50/GU24	Natural White GU24	10/50	5000	82	1600	100	10000	4.41"	2.13"
T3	Med.	✓ 45250	*CFL23/27	Warm White	10/50	2700	82	1600	100	12000	5.75"	2.13"
T3	Med.	✓ 46334	CFL23/27/DIM	Warm White Dimmable	10/50	2700	82	1600	100	10000	5.59"	2.13"
T3	Med.	45252	*CFL23/35	White	10/50	3500	82	1600	100	12000	5.04"	2.05"
T3	Med.	45253	*CFL23/41	Cool White	10/50	4100	82	1600	100	12000	5.04"	2.05"
T3	Med.	45254	*CFL23/50	Natural White	10/50	5000	82	1600	100	12000	5.04"	2.05"
T3	GU24	46548	CFL23/27/GU24/DIM	Warm White Dimmable	10/50	2700	82	1600	100	10000	4.73"	2.36"
<b>26 Watts</b>												
T2	Med.	45080	CFL26/27/T2	Warm White	10/50	2700	82	1750	100	10000	5.08"	2.13"
T2	Med.	45081	CFL26/35/T2	White	10/50	3500	82	1750	100	10000	5.08"	2.13"
T2	Med.	45082	CFL26/41/T2	Cool White	10/50	4100	82	1750	100	10000	5.08"	2.13"
T2	Med.	45083	CFL26/50/T2	Natural White	10/50	5000	82	1750	100	10000	5.08"	2.13"
T3	GU24	✓ 46528	*CFL26/27/GU24	Warm White GU24	10/50	2700	82	1750	100	10000	5.20"	2.13"
T3	GU24	46531	*CFL26/35/GU24	White GU24	10/50	3500	82	1750	100	10000	5.20"	2.13"
T3	GU24	46529	*CFL26/41/GU24	Cool White GU24	10/50	4100	82	1750	100	10000	5.20"	2.13"
T3	GU24	46530	*CFL26/50/GU24	Natural White GU24	10/50	5000	82	1750	100	10000	5.20"	2.13"
<b>27 Watts</b>												
T3	Med.	✓ 109310	CFL27/27	Warm White	10/50	2700	82	1900	100	10000	5.44"	2.44"
T3	Med.	45255	CFL27/35	White	10/50	3500	82	1850	100	10000	5.44"	2.44"
T3	Med.	109312	CFL27/41	Cool White	10/50	4100	82	1850	100	10000	5.44"	2.44"
T3	Med.	109314	CFL27/50	Natural White	10/50	5000	82	1750	100	10000	5.44"	2.44"
<b>32 Watts</b>												
T3	Med.	✓ 109316	CFL32/27	Warm White	10/50	2700	82	2250	125	8000	5.56"	2.76"
T3	Med.	109318	CFL32/41	Cool White	10/50	4100	82	2200	125	8000	5.56"	2.76"
T3	Med.	109306	CFL32/50	Natural White	10/50	5000	82	2200	125	8000	5.56"	2.76"
<b>42 Watts</b>												
T3	Med.	✓ 109328	CFL42/27	Warm White	6/24	2700	82	2900	150	12000	7.06"	2.83"
T3	Med.	109336	CFL42/41	Cool White	6/24	4100	82	2800	150	12000	7.06"	2.83"
T3	Med.	109338	CFL42/50	Natural White	6/24	5000	82	2800	150	12000	7.06"	2.83"
<b>65 Watts</b>												
T5	Med.	45600	CFL65/27	Warm White	1/6	2700	82	4300	300	10000	9.50"	3.54"
T5	Med.	45604	CFL65/50	Natural White	1/6	5000	82	4300	300	10000	9.50"	3.54"
<b>85 Watts</b>												
T5	Med.	45606	CFL85/27	Warm White	1/6	2700	82	5700	400	10000	10.00"	4.02"
T5	Med.	45610	CFL85/50	Natural White	1/6	5000	82	5700	400	10000	10.00"	4.02"
T5	Med.	45500	CFL85/50/E39	Natural White	1/6	5000	82	5700	400	10000	10.50"	4.02"
<b>105 Watts</b>												
T5	Med.	45618	CFL105/50	Natural White	1/6	5000	82	7000	500	10000	10.75"	4.02"
T5	Med.	45502	CFL105/50/277V	Natural White 277V	1/6	5000	82	7000	500	10000	10.75"	4.02"
T5	Mog.	45614	CFL105/50/E39	Natural White	1/6	5000	82	7000	500	10000	11.25"	4.02"
T5	Mog.	45504	CFL105/50/E39/277V	Natural White 277V	1/6	5000	82	7000	500	10000	11.25"	4.02"
<b>150 Watts</b>												
⊕ T6	EX39	47000	CFL150/50/EX39	Natural White	1/6	5000	82	8800	250 MH	10000	13.03"	4.72"
<b>180 Watts</b>												
⊕ T6	EX39	47001	CFL180/50/EX39	Natural White	1/6	5000	82	11100	400 MH	10000	14.33"	4.72"

# ProLume. Bare Spirals - Quick Reference Guide



Bulb Type	Base	Product #	Product Code	Description	Pkg Qty	Color Temp	CRI	Initial Lumens	Incandescent Equivalent	Life	MOL (Inc)	MOD (Inc)
-----------	------	-----------	--------------	-------------	---------	------------	-----	----------------	-------------------------	------	-----------	-----------

**NEW ITEM!**

✓ Represents lamps that are Energy Star approved.

\* UL approved for totally enclosed fixtures with a max ballast case temperature of 90°C for GU24 base lamps, 75°C for medium base lamps.

Hg-Lamp Contains Mercury, Manage In Accord With Disposal Laws.

Non-dimmable lamps should not be used on dimming circuits, timing devices, photo sensors or occupancy sensors. | This device is not intended for use with emergency exit fixtures.  
Dimmable lamps may not be compatible with all dimmers.



Halco Lighting Technologies | P.O. Box 2834 | Norcross, GA 30091-2834 | Toll Free 800.677.3334 | Phone 770.242.3612 | Fax 800.880.0822 | [halcolighting.com](http://halcolighting.com) | Atlanta | Carlstadt | Cleveland | Houston | Phoenix  
 © 2013 Halco Lighting Technologies, LLC. All rights reserved. "where there's light, there's halco" and Halco are registered trademark of Halco Lighting Technologies. All product names are trademarks or registered trademarks of Halco Lighting Technologies. All sizes and specifications are subject to change. Online Edition 02-04-14.