



# BR/R LED

## 7.2BR30/PER/927/P/E26/DIM 6/1FB T20

Philips Dimmable LED Reflector Lamps provide a soft, diffused level of light and smooth dimming to reduce glare. The sleek, lightweight design is ideal for downlighting.

### Product data

General Information	
Base	E26 [ Single Contact Medium Screw]
Nominal Lifetime (Nom)	15000 h
Switching Cycle	50000X
Technical Type	7.2-65W
Light Technical	
Color Code	927
Beam Angle (Nom)	110 °
Initial lumen (Nom)	650 lm
Luminous Flux (Rated) (Nom)	650 lm
Color Designation	Warm White (WW)
Correlated Color Temperature (Nom)	2700 K
Luminous Efficacy (rated) (Nom)	90.00 lm/W
Color Consistency	<4
Color Rendering Index (Nom)	90
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Input Frequency	60 Hz
Power (Rated) (Nom)	7.2 W
Lamp Current (Nom)	82 mA
Wattage Equivalent	65 W
Starting Time (Nom)	0.5 s

Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.7
Voltage (Nom)	120 V
Temperature	
T-Case Maximum (Nom)	70 °C
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb Finish	Frosted
Product Data	
Order product name	7.2BR30/PER/927/P/E26/DIM 6/1FB T20
EAN/UPC - Product	046677553890
Order code	553891
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material Nr. (12NC)	929002092304
Net Weight (Piece)	0.095 kg



# BR/R LED

## Dimensional drawing

Product	D	C
7.2BR30/PER/927/P/E26/DIM 6/1FB T20	95 mm	132 mm


BR30 120V 7.2-65W 650lm 2700K E26 D

## Photometric data



LEDbulb 65W E26 BR30 927 Frosted

LEDbulb 65W E26 BR30 927 Frosted



LEDbulb 65W E26 BR30 927 Frosted

## BR/R LED

### Lifetime



LEDbulb\_15K LED



LEDbulb\_15K LMP

