

I. Product Description

CRC Spray Adhesive is a low VOC, general purpose, quick tack adhesive especially formulated to bond to many foils, plastics, papers, foams, metals, cardboards and cloths.

II. Applications

Recommended for labeling boxes and machinery, sealing and re-sealing boxes and packages for shipment, hanging insulation, repair of furniture and display materials as well as general interior maintenance.

III. Features & Benefits

- Minimal soak-in
- High tack formula
- California VOC Compliant
- Good water resistance
- Versatile enough to create both high strength and temporary bonds

IV. Physical Properties

Flash Point	-156°F TCC	Boiling Point	-44-177°F
Odor	Mint when wet	Freezing Point	ND
Appearance	White liquid	Solubility	Negligible in water
Vapor Density	>1 (air = 1)	% Solids	17 +/- 1.5
VOC Content (Fed)	455 g/L	VOC %	63.9
Sara Title III, Sect. 313 Chemicals	Yes	Specific Gravity	0.7138
Prop 65	Yes		

V. Specifications and Approvals

- N/A

VI. Directions

1. Shake well before using.
2. Always direct spray tip toward the surface to be bonded.
3. Hold can 6-8 inches away from surface to be sprayed.
4. Apply a light uniform coat of adhesive to surface.
5. For POROUS substrates, apply two coats in opposite directions.
6. For PERMANENT bonds, apply a heavy coat to both surfaces, let dry for 3 to 5 minutes and press substrates together.
7. For NON-PERMANENT bonds, apply a light coating to one surface only, let dry for 5 minutes and bond.
8. After use, invert can and depress spray tip until spray is free of adhesive.
9. If clogged, clean with petroleum distillate.
10. Use caution when using on or around energized equipment.

VII. Package Description

Part Number	Container Size
03018	24 oz Aerosol

VIII. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations. DO NOT dump in sewers, floor drains, on the ground or into any body of water.

IX. Special Use Warnings

General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short-term and long-term exposure, review the Material Safety Data Sheet for this product.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular application prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data.

CRC Industries, Inc.
Technical Service: (800)521-3168

Industrial Products Division
Customer Service: (800)272-4620

Warminster, PA 18974
CRC On-Line: (215)442-6260