

Anaerobic Connector, LC 62.5 μm multimode (OM1)

CORNING

Part Number:
95-101-98-SP

Corning anaerobic-cured connectors offer optical performance in a fast, easy field-termination solution designed for fiber-to-the-workstation applications for single-mode and multimode connections. This connector combines the quick-cured convenience of anaerobic adhesive with the performance of epoxy-and-polish connectors. Ideal for enterprise networks and any installations requiring field-installed connectors, the anaerobic-cured technology enables fiber optic networks to be installed cost effectively with minimal tools. Installation of the connector can be accomplished in minutes with the anaerobic adhesive two-part epoxy process. The adhesive is first injected into the connector ferrule, and then the fiber is dipped into the primer and inserted into the connector. Curing takes only one minute without the use of lamps or ovens. With the hand-polish process, an average insertion loss of 0.2 dB is achieved.

Features and Benefits

Quick-cure epoxy

No lamps or ovens needed

Minimal tools and no index-matching gel

Low installation cost

Hand polished for minimum insertion loss

Reliability and optical performance



Anaerobic Connector, LC, 62.5 μm multimode (OM1)

Anaerobic Connector, LC 62.5 μm multimode (OM1)



Specifications

Design - Connector	
Connector Type	LC
Housing Color	Beige
Housing Material	Composite
Boot Color	Beige

General Specifications	
Fiber Category	62.5 μm MM (OM1)
Product Type	Field-Installable Connectors
Corning Logo	Yes
Keyed (security)	No
Technology	Field Polish (anaerobic)

Optical Specifications - Connector	
Insertion Loss, Max.	0.75 dB
Reflectance	≤ -26 dB
Insertion Loss, Typical	≤ 0.1 dB

Ordering Information	
Product Number	95-101-98-SP
EAN Code	4056418201238
Packaging	Individual Pack
Package Contents	Connector, Trigger, Crimp Band (1.6/2.0 mm), Crimp Band (3.0 mm), Boot (900 μm), Boot (2.0 mm), Boot (3.0 mm)
Units per Delivery	1/1

Anaerobic Connector, LC 62.5 μ m multimode (OM1)



Standards

RoHS	Free of hazardous substances according to RoHS 2011/65/EU
------	---



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2021 Corning Optical Communications. All rights reserved.