



Representative Image

Catalog No. 9T10A1184

Description: 75KVA 3P AL 480-240/120 150C DOE

UPC No 783173903933

Home > Transformers > Dry Type Vented > General Purpose

GE Type QL transformers meet DOE 2016 efficiency standards. They are available with aluminum or copper windings and utilize a UL recognized 220 degree centigrade insulation system. -Quiet Performance-Outward-facing mounting feet-Lug kit included-Ground bar kit included-Core and coil assemblies are mounted on rubber isolation pads to reduce noise-Bolted coil terminations-Single-piece front/back is easily removable for service-NEMA 2 drip-proof enclosure is standard weathershield kits are available for conversion to NEMA 3R outdoor configuration-Qualified to the seismic requirements of IEEE-693-2005 and IBC-2012 and CBC 2013-Copper or aluminum windings-Copper ground strap-Robust packaging with top and side protection protects against shipping damage-Accessible mounting flanges with front/back slotted mounting holes make installation easier-100 percentage factory tested for shorts and coil integrity, current and loss, voltage, impedance and noise.-Clear, comprehensive documentation and labeling 10A1184

Descriptors

Category | Dry Type Vented

Specifications

Phase	3
PriVoltage	480
SecVoltage	240/120
KVA	75.0 KVA
Coil Material	AL
TempRise	150.0 °C
Frequency	60 Hz
Impedance	5.6 %
AmbTemp	40.0 °C
EnergyEfficiency	DOE 2016
KFactor	K1
Enclosure Type	NEMA 2
Sound	Std
GSA Compliance	No

Publications

Title	Publication No.	Publication Type
UL Nameplate Drawing		
UL Nameplate Drawing 9T10A1184-LBL	9T10A1184-LBL	Connection Diagram

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.