

Screw Connection Terminal Blocks

Plug-In Style Terminal Blocks

	1492-J3P			1492-J3PTP			1492-JD3P		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
Specifications	Selectable component plug-in terminal block			Selectable component plug-in terminal block with test plug socket			Two Circuit selectable component plug-in terminal block		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating	600V AC/DC	300V AC/DC	500V AC/DC	300V AC/DC		500V AC/DC	300V AC/DC		500V AC/DC
Maximum Current	20 A	10 A	24 A	20 A	10 A	24 A	20 A	24 A	24 A
Wire Range (Rated Cross Section)	#30...12 AWG		2.5 mm ²	#30...12 AWG		2.5 mm ²	#24...12 AWG	#30...12 AWG	2.5 mm ²
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)			0.31 in. (8 mm)		
Recommended Tightening Torque	4.4 lb•in (0.5 N•m)			4.4 lb•in (0.5 N•m)			4.4 lb•in (0.5 N•m)		
Density	59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Short-Circuit Current Rating	See page 12-42								
Terminal Blocks		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.
Color:	Grey	1492-J3P	100		1492-J3PTP	100		1492-JD3P	50
	Red	1492-J3P-RE	100		—	—		—	—
Accessories		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.
Mounting Rails:									
1 m Symmetrical DIN (Steel)		199-DR1	10		199-DR1	10		199-DR1	10
1 m Symmetrical DIN (Aluminum)		1492-DR5	10		1492-DR5	10		1492-DR5	10
1 m Hi-Rise Sym. DIN (Aluminum)		1492-DR6	2		1492-DR6	2		1492-DR6	2
1 m Angled Hi-Rise Sym. DIN (Steel)		1492-DR7	2		1492-DR7	2		1492-DR7	2
End Barriers		1492-EBJ3	50		1492-EBJ3	50		1492-EBJD3P	20
End Anchors and Retainers:		1492-ERL35	20		1492-ERL35	20		1492-ERL35	20
Screwless End Retainer									
DIN Rail — Normal Duty		1492-EAJ35	100		1492-EAJ35	100		1492-EAJ35	100
DIN Rail — Heavy Duty		1492-EAHJ35	50		1492-EAHJ35	50		1492-EAHJ35	50
Jumpers* †:		1492-CJLJ5-50	10		1492-CJLJ5-50	10		—	—
Center Jumper — 50-Pole									
Center Jumper — 10-Pole		1492-CJLJ5-10	20		1492-CJLJ5-10	20		1492-CJJ5-10	20
Center Jumper — 9-Pole		1492-CJLJ5-9	20		1492-CJLJ5-9	20		—	—
Center Jumper — 8-Pole		1492-CJLJ5-8	20		1492-CJLJ5-8	20		—	—
Center Jumper — 7-Pole		1492-CJLJ5-7	20		1492-CJLJ5-7	20		—	—
Center Jumper — 6-Pole		1492-CJLJ5-6	20		1492-CJLJ5-6	20		—	—
Center Jumper — 5-Pole		1492-CJLJ5-5	20		1492-CJLJ5-5	20		—	—
Center Jumper — 4-Pole		1492-CJLJ5-4	60		1492-CJLJ5-4	60		1492-CJJ5-4	50
Center Jumper — 3-Pole		1492-CJLJ5-3	60		1492-CJLJ5-3	60		1492-CJJ5-3	50
Center Jumper — 2-Pole		1492-CJLJ5-2	60		1492-CJLJ5-2	60		1492-CJJ5-2	50
Screw Type Jumper Notching Tool		—	—		—	—		1492-T1	1
Other Accessories:		1492-EBJ16	20		1492-EBJ16	20		1492-PPJD3P	20
Partition Plate									
Test Plug		—	—		1492-TP23	20		—	—
Disconnect Plug		1492-DPL	50		1492-DPL	50		1492-DPL	50
Component Plug		1492-CPL	50		1492-CPL	50		1492-CPL	50
Fuse Plug		1492-FPK2	20		1492-FPK2	20		1492-FPK2	20
Without Blown Fuse Indicator									
10...36V Blown Fuse Indicator		1492-FPK224	20		1492-FPK224	20		1492-FPK224	20
35...70V Blown Fuse Indicator		1492-FPK248	20		1492-FPK248	20		1492-FPK248	20
60...150V Blown Fuse Indicator		1492-FPK2120	20		1492-FPK2120	20		1492-FPK2120	20
140...250V Blown Fuse Indicator		1492-FPK2250	20		1492-FPK2250	20		1492-FPK2250	20
Marking Systems:		1492-M5X12 (144/card)	5		1492-M5X12 (144/card)	5		1492-SM5X10 (144/card)	5
Snap-in marker cards									
Snap-in marker cards		1492-M5X5 (200/card)	5		1492-M5X5 (200/card)	5		1492-M5X5 (200/card)	5













* Cat. nos. 1492-J3P and J3PTP use screwless center jumpers. Cat. No. 1492-JD3P uses a screw-type center jumper.

† Use of Center Jumpers may affect spacings, requiring derating of terminal blocks. See the Terminal Block selection guide, pub. no. 1492-SG008*.



Screw Connection Terminal Blocks

Plug-In Style Terminal Blocks

	1492-JD3PTP			1492-JD3PSS			1492-JD3PSSTP		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
Specifications	<i>Two-circuit selectable component plug-in terminal block with test plug socket</i>			<i>Two-circuit selectable component plug-in terminal block with internal surge suppressor</i>			<i>Two-circuit selectable component plug-in terminal block with internal surge suppressor and test plug socket</i>		
Certifications									
Voltage Rating	300V AC/DC		500V AC/DC	300V AC/DC		115V AC	300V AC/DC		115V AC/DC
Maximum Current	20 A		24 A	20 A		24 A	20 A		24 A
Wire Range (Rated Cross Section)	#24...12 AWG	#30...12 AWG	2.5 mm ²	#24...12 AWG	#30...12 AWG	2.5 mm ²	#24...12 AWG	#30...12 AWG	2.5 mm ²
Wire Strip Length	0.31 in. (8 mm)			0.31 in. (8 mm)			0.31 in. (8 mm)		
Recommended Tightening Torque	4.4 lb•in (0.5 N•m)			4.4 lb•in (0.5 N•m)			4.4 lb•in (0.5 N•m)		
Density	59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Short-Circuit Current Rating	See page 12-42								
Terminal Blocks	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.
Color: Grey	1492-JD3PTP	50	1492-JD3PSS	50	1492-JD3PSSTP	50			
Accessories	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.
Mounting Rails:									
1 m Symmetrical DIN (Steel)	199-DR1	10	199-DR1	10	199-DR1	10			
1 m Symmetrical DIN (Aluminum)	1492-DR5	10	1492-DR5	10	1492-DR5	10			
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2	1492-DR6	2	1492-DR6	2			
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2	1492-DR7	2	1492-DR7	2			
End Barriers	1492-EBJD3P	20	1492-EBJD3P	20	1492-EBJD3P	20			
End Anchors and Retainers:									
Screwless End Retainer	1492-ERL35	20	1492-ERL35	20	1492-ERL35	20			
DIN Rail — Normal Duty	1492-EAJ35	100	1492-EAJ35	100	1492-EAJ35	100			
DIN Rail — Heavy Duty	1492-EAHJ35	50	1492-EAHJ35	50	1492-EAHJ35	50			
Jumpers:									
Screw Center Jumper — 10-Pole	1492-CJJ5-10	20	1492-CJJ5-10	20	1492-CJJ5-10	20			
Screw Center Jumper — 4-Pole	1492-CJJ5-4	50	1492-CJJ5-4	50	1492-CJJ5-4	50			
Screw Center Jumper — 3-Pole	1492-CJJ5-3	50	1492-CJJ5-3	50	1492-CJJ5-3	50			
Screw Center Jumper — 2-Pole	1492-CJJ5-2	50	1492-CJJ5-2	50	1492-CJJ5-2	50			
Screw Type Jumper Notching Tool	1492-T1	1	1492-T1	1	1492-T1	1			
Other Accessories:									
Partition Plate	1492-PPJD3P	20	1492-PPJD3P	20	1492-PPJD3P	20			
Test Plug	1492-TP23	20	—	—	1492-TP23	20			
Disconnect Plug	1492-DPL	50	1492-DPL	50	1492-DPL	50			
Component Plug	1492-CPL	50	1492-CPL	50	1492-CPL	50			
Fuse Plug									
Without Blown Fuse Indicator	1492-FPK2	20	1492-FPK2	20	1492-FPK2	20			
10...36V Blown Fuse Indicator	1492-FPK224	20	1492-FPK224	20	1492-FPK224	20			
35...70V Blown Fuse Indicator	1492-FPK248	20	1492-FPK248	20	1492-FPK248	20			
60...150V Blown Fuse Indicator	1492-FPK2120	20	1492-FPK2120	20	1492-FPK2120	20			
140...250V Blown Fuse Indicator	1492-FPK2250	20	1492-FPK2250	20	1492-FPK2250	20			
Group Marking Carrier	1492-GM35	25	1492-GM35	25	1492-GM35	25			
Marking Systems:									
Snap-in marker cards	1492-SM5X10 (144/card)	5	1492-SM5X10 (144/card)	5	1492-SM5X10 (144/card)	5			
Snap-in marker cards	1492-M5X5 (200/card)	5	1492-M5X5 (200/card)	5	1492-M5X5 (200/card)	5			

Screw Connection Terminal Blocks

Double-Level Plug-In Style Terminal Blocks

	1492-JDG3P			1492-JDG3PTP			1492-JDG3PSS		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
Specifications	<i>Two-circuit block with ground connection</i>			<i>Two-circuit block with test plug socket and ground connection</i>			<i>Single-circuit block with MOV to ground</i>		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating	300V AC/DC		500V AC/DC	300V AC/DC		500V AC/DC	300V AC/DC		115V AC
Maximum Current	20 A			20 A			20 A		
Wire Range (Rated Cross Section)	#24...12 AWG	#30...12 AWG	2.5 mm ²	#24...12 AWG	#30...12 AWG	2.5 mm ²	#24...12 AWG	#30...12 AWG	2.5 mm ²
Wire Strip Length	0.31 in. (8 mm)			0.31 in. (8 mm)			0.31 in. (8 mm)		
Recommended Tightening Torque	4.4 lb•in (0.5 N•m)			4.4 lb•in (0.5 N•m)			4.4 lb•in (0.5 N•m)		
Density	59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Short-Circuit Current Rating	See page 12-42								
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Color: Grey	1492-JDG3P	50		1492-JDG3PTP	50		1492-JDG3PSS	50	
Accessories	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Mounting Rails:									
1 m Symmetrical DIN (Steel)	199-DR1	10		199-DR1	10		199-DR1	10	
1 m Symmetrical DIN (Aluminum)	1492-DR5	10		1492-DR5	10		1492-DR5	10	
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6	2		1492-DR6	2		1492-DR6	2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2		1492-DR7	2		1492-DR7	2	
End Barriers	1492-EBJD3P	20		1492-EBJD3P	20		1492-EBJD3P	20	
End Anchors and Retainers:									
Screwless End Retainer	1492-ERL35	20		1492-ERL35	20		1492-ERL35	20	
DIN Rail — Normal Duty	1492-EAJ35	100		1492-EAJ35	100		1492-EAJ35	100	
DIN Rail — Heavy Duty	1492-EAHJ35	50		1492-EAHJ35	50		1492-EAHJ35	50	
Jumpers:									
Screw Center Jumper — 10-Pole	1492-CJJ5-10	20		1492-CJJ5-10	20		—	—	
Screw Center Jumper — 4-Pole	1492-CJJ5-4	50		1492-CJJ5-4	50		—	—	
Screw Center Jumper — 3-Pole	1492-CJJ5-3	50		1492-CJJ5-3	50		—	—	
Screw Center Jumper — 2-Pole	1492-CJJ5-2	50		1492-CJJ5-2	50		—	—	
Screw Type Jumper Notching Tool	1492-T1	1		1492-T1	1		—	—	
Other Accessories:									
Partition Plate	1492-PPJD3P	20		1492-PPJD3P	20		1492-PPJD3P	20	
Test Plug	—	—		1492-TP23	20		—	—	
Disconnect Plug	1492-DPL	50		1492-DPL	50		1492-DPL	50	
Component Plug	1492-CPL	50		1492-CPL	50		1492-CPL	50	
Fuse Plug									
Without Blown Fuse Indicator	1492-FPK2	20		1492-FPK2	20		1492-FPK2	20	
10...36V Blown Fuse Indicator	1492-FPK224	20		1492-FPK224	20		1492-FPK224	20	
35...70V Blown Fuse Indicator	1492-FPK248	20		1492-FPK248	20		1492-FPK248	20	
60...150V Blown Fuse Indicator	1492-FPK2120	20		1492-FPK2120	20		1492-FPK2120	20	
140...250V Blown Fuse Indicator	1492-FPK2250	20		1492-FPK2250	20		1492-FPK2250	20	
Marking Systems:									
Snap-in marker cards	1492-SM5X10 (144/card)	5		1492-SM5X10 (144/card)	5		1492-SM5X10 (144/card)	5	
Snap-in marker cards	1492-M5X5 (200/card)	5		1492-M5X5 (200/card)	5		1492-M5X5 (200/card)	5	


Screw Connection Terminal Blocks

Double-Level Plug-In Style Terminal Blocks

1492-JDG3PSSTP

Dimensions are not intended to be used for manufacturing purposes.

Note: Height dimension is measured from top of rail to top of terminal block.



Specifications	Single-circuit block with MOV to ground and test plug socket		
Certifications		CSA	IEC
Voltage Rating	300V AC/DC		115V AC
Maximum Current	20 A		24 A
Wire Range (Rated Cross Section)	#24...12 AWG	#30...12 AWG	2.5 mm ²
Wire Strip Length	0.31 in. (8 mm)		
Recommended Tightening Torque	4.4 lb•in (0.5 N•m)		
Density	59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)		
Short-Circuit Current Rating	See page 12-42		
Terminal Blocks	Cat. No.		Pkg Qty.
Color: Grey	1492-JDG3PSSTP		50
Accessories	Cat. No.		Pkg Qty.
Mounting Rails:			
1 m Symmetrical DIN (Steel)	199-DR1		10
1 m Symmetrical DIN (Aluminum)	1492-DR5		10
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR6		2
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7		2
End Barriers	1492-EBJD3P		20
End Anchors and Retainers:			
Screwless End Retainer	1492-ERL35		20
DIN Rail — Normal Duty	1492-EAJ35		100
DIN Rail — Heavy Duty	1492-EAHJ35		50
Other Accessories:			
Partition Plate	1492-PPJD3P		20
Test Plug	1492-TP23		20
Disconnect Plug	1492-DPL		50
Component Plug	1492-CPL		50
Fuse Plug			
Without Blown Fuse Indicator	1492-FPK2		20
10...36V Blown Fuse Indicator	1492-FPK224		20
35...70V Blown Fuse Indicator	1492-FPK248		20
60...150V Blown Fuse Indicator	1492-FPK2120		20
140...250V Blown Fuse Indicator	1492-FPK2250		20
Marking Systems:			
Snap-in marker cards	1492-SM5X10 (144/card)		5
Snap-in marker cards	1492-M5X5 (200/card)		5

Spring-Clamp Connection Terminal Blocks

Plug-In Style Blocks & Analog Loop Control Block











	1492-L3P			1492-LDG3P			1492-LDAG3		
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.									
Specifications	Single circuit plug-in component block for a variety of components			Terminal block with slot for plug-in component, feed-through circuit and 1 ground connection			Analog Loop Control Terminal Block with 2 Feed-Through Circuits and 1 Ground Connection		
Certifications		CSA	IEC		CSA	IEC		CSA	IEC
Voltage Rating	600V AC/DC		500V AC/DC	300V AC/DC		250V AC/DC	300V AC/DC		250V AC/DC
Maximum Current	20 A		24 A	10 A		20 A	10 A		24 A
Wire Range (Rated Cross Section)	#30...12 AWG		4 mm ²	#26...12 AWG		2.5 mm ²	#26...12 AWG		2.5 mm ²
Wire Strip Length	0.39 in. (10 mm)			0.31 in. (8 mm)			0.31 in. (8 mm)		
Density	59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)			59 pcs/ft (196 pcs/m)		
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)		
Terminal Blocks	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Color	Grey	1492-L3P	25	1492-LDG3P	25		1492-LDAG3	25	
Accessories	Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.		Cat. No.	Pkg Qty.	
Mounting Rails									
1 m Symmetrical DIN (Steel)	199-DR1	10		199-DR1	10		199-DR1	10	
1 m Symmetrical DIN (Aluminum)	1492-DR5	10		1492-DR5	10		1492-DR5	10	
1 m Hi-Rise Symmetrical DIN (Aluminum)	1492-DR6	2		1492-DR6	2		1492-DR6	2	
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2		1492-DR7	2		1492-DR7	2	
End Barrier	1492-EBL3	50		1492-EBLDAG3	20		1492-EBLDAG3	20	
End Anchors and Retainers									
Screwless End Retainer	1492-ERL35	20		1492-ERL35	20		1492-ERL35	20	
DIN Rail — Normal Duty	1492-EAJ35	100		1492-EAJ35	100		1492-EAJ35	100	
DIN Rail — Heavy Duty	1492-EAHJ35	50		1492-EAHJ35	50		1492-EAHJ35	50	
Jumpers									
Plug-In Center Jumper — 50-pole	1492-CJK5-50	10		1492-CJLJ5-50	10		1492-CJLJ5-50	10	
Plug-In Center Jumper — 10-pole	1492-CJK5-10	20		1492-CJLJ5-10	20		1492-CJLJ5-10	20	
Plug-In Center Jumper — 9-pole	1492-CJK5-9	20		1492-CJLJ5-9	20		1492-CJLJ5-9	20	
Plug-In Center Jumper — 8-pole	1492-CJK5-8	20		1492-CJLJ5-8	20		1492-CJLJ5-8	20	
Plug-In Center Jumper — 7-pole	1492-CJK5-7	20		1492-CJLJ5-7	20		1492-CJLJ5-7	20	
Plug-In Center Jumper — 6-pole	1492-CJK5-6	20		1492-CJLJ5-6	20		1492-CJLJ5-6	20	
Plug-In Center Jumper — 5-pole	1492-CJK5-5	20		1492-CJLJ5-5	20		1492-CJLJ5-5	20	
Plug-In Center Jumper — 4-pole	1492-CJK5-4	60		1492-CJLJ5-4	60		1492-CJLJ5-4	60	
Plug-In Center Jumper — 3-pole	1492-CJK5-3	60		1492-CJLJ5-3	60		1492-CJLJ5-3	60	
Plug-In Center Jumper — 2-pole	1492-CJK5-2	60		1492-CJLJ5-2	60		1492-CJLJ5-2	60	
Other Accessories									
Disconnect Plug	1492-DPL	50		1492-DPL	50		—	—	
Component Plug	1492-CPL	50		1492-CPL	50		—	—	
Fuse Plug									
Without Blown Fuse Indicator	1492-FPK2	20		1492-FPK2	20		—	—	
10...36V Blown Fuse Indicator	1492-FPK224	20		* 1492-FPK224	20		—	—	
35...70V Blown Fuse Indicator	1492-FPK248	20		* 1492-FPK248	20		—	—	
60...150V Blown Fuse Indicator	1492-FPK2120	20		* 1492-FPK2120	20		—	—	
140...250V Blown Fuse Indicator	1492-FPK2250	20		* 1492-FPK2250	20		—	—	
Reducing Sleeves 28...24 AWG (0.13...0.2 mm ²) White	1492-PSL3-2	100		—	—		—	—	
Reducing Sleeves 22...20 AWG (0.25...0.5 mm ²) Grey	1492-PSL3-5	100		—	—		—	—	
Reducing Sleeves 18 AWG (0.75...1.0 mm ²) Dark Grey	1492-PSL3-10	100		—	—		—	—	
Test Plug	1492-TPL5	25		1492-TP23	20		—	—	
Electrical Warning Plate	1492-EWPL5	20		—	—		—	—	
Marking Systems									
Snap-In Marker Cards	1492-M5X10 (144/card)	5		1492-M5X10 (144/card)	5		1492-M5X10 (144/card)	5	
Snap-In Marker Cards	1492-M5X5 (200/card)	5		1492-M5X5 (200/card)	5		1492-M5X5 (200/card)	5	

* When using Cat. No. 1492-LDG3P with a fuse plug, a center jumper cannot be used on the top level. The only jumper option to use in combination with a fuse plug is a 2-pole side jumper: Cat. No. 1492-SJLM5-2.



IEC Terminal Block Accessories

General Accessories

Photo	Description	For Use With	Pkg Qty.	Cat. No.
	Jumper Notching Tool*	1492-CJ...	1	1492-T1
	Unused Pin Cover on Connection Blocks	1492-JC3, JDC3	20	1492-PCJC3
	Disconnect Plug	1492-L3P, J3P..., JD3P..., JDG3P..., LD3R...	50	1492-DPL
	Plug-In Component Plug	1492-L3P, J3P..., JD3P..., JDG3P..., LD3R...	50	1492-CPL
	Fuse Plug — without Blown Fuse Indication	1492-L3P, J3P..., JD3P..., JDG3P..., LD3R...	20	* 1492-FPK2
	Fuse Plug — 10...36V Blown Fuse Indication		20	* 1492-FPK224
	Fuse Plug — 35...70V Blown Fuse Indication		20	* 1492-FPK248
	Fuse Plug — 60...150V Blown Fuse Indication		20	* 1492-FPK2120
	Fuse Plug — 140...250V Blown Fuse Indication		20	* 1492-FPK2250
	Mini-Block Jumper Insertion Tool†	1492-LM	1	1492-TAL5-2
	DIN Rail Adapter Plate for LMP3 Mini-Blocks	1492-LMP3	50	1492-MFLM
	Auxiliary Circuit Tap	1492-J50	5	1492-J50A
		1492-J70	5	1492-J70A
		1492-J120	5	1492-J120A
	Terminal Block screwdriver with hardened 3mm diameter blade (Handle made from recycled material)	All 5...6 mm wide terminal blocks	5	1492-N90
	Wire cutting tool designed to attach directly to the shaft of the Cat. No. 1492-N90 screwdriver	1492-N90	1	1492-KWC

* Used to trim poles from center jumpers and side jumpers.

† Used to install Cat. No. 1492-SJLM5-2 in mini blocks.

* Use 5 x 20 mm fuses and are rated for AC and DC.

