

Bulletin 1492 DIN Rail Receptacle

Advantages

- Quick to snap on 35 mm DIN rail and easy to wire
- Available with ground fault current interrupt (GFCI) or standard duplex outlets
- Feature of visual indication of power included with GFCI receptacle



1492-REC15G
GFCI Receptacle



1492-REC15
Standard Duplex Receptacle

Overview

The Bulletin 1492 DIN rail receptacle is an enclosed 15 Amp power outlet. It is a convenient power source for portable computers or test devices for in-the-panel troubleshooting.

Technical Specifications for the DIN Rail Receptacle		Dimensions
	1492-REC15	
Mechanical Ratings		
	15 Amp Duplex	15 Amp GFCI
Operating Temperatures	-13°F to 140°F (-25°C to 60°C)	
Storage Temperatures, Short Term	-31°F to 176°F (-35°C to 80°C)	
Terminal Wire Sizes	#20 - #10 AWG solid or stranded	
Terminal Torque	7 lb.-in. (.79 Nm)	
Electrical Ratings		
Device Ratings	15 Amp, 125V	15 Amp, 125V
Operating Frequency	50 - 60 Hz	
Dielectric Voltage	Withstands 2000V per UL498	Withstands 1500V per UL498
Current Interrupting	N/A	10 kA
Trip Level	N/A	5±1 mA
Material Listing		
Enclosure Cover, Flammability	PBT/polycarbonate blend, UL94 rating V0 @ .63mm	
Enclosure Base, Flammability	Polyamide 6/6 30% GF, UL94 rating V0 @ .63mm	
Spring	Stainless Steel	
Standards and Certifications		
	UL 508A (file # E54866)	
	cULus	
	UL498	UL 498, UL 943
	NEMA WD-6	
	NEMA 5-15R	

4.9" (123.6mm)

4.6" (116.3mm)

2.9" (74.1mm)

	Cat. No.	Pkg. Qty.
Marking Systems Marker Card:	1492-MS10x17 (40/card)	5

