


Heavy Duty Safety Disconnect Switches

Product Overview/Product Selection — Fusible and Non-Fusible Type

	<p>Bulletin 1494H Heavy Duty Safety Switches</p> <ul style="list-style-type: none"> • 30...200 A switch ratings • Type 1, 3R, or 12 enclosures • 600V: 1-phase, 3-phase, non-fusible • 240V: 1-phase, 3-phase, fusible • 600V: 3-phase, fusible • Visible blade construction for safety • Side-mounted metal handle • Lockable handle • Can accommodate Class H, R, and J fuses • Accessories — field installed 	<p>Table of Contents</p> <p>Product Selection..... this page Accessories..... 1-224</p> <p>Standards Compliance UL 98 CSA C22.2, No. 4</p> <p>Certifications UL Listed (File No. E227497, Guide No. WIAX) CSA Certified (File No. LR1234)</p>
---	--	---



Non-Fusible Disconnect Switch (600V AC)

Continuous Current Rating [A]	UL & CSA Application Horsepower (Maximum)						Type 1 Cat. No.	Type 3R Cat. No.	Type 12 Cat. No.	
	1-Phase (60 Hz)		3-Phase (60 Hz)			3-Phase (60 Hz)				
	240V AC		240V AC	480V AC	600V AC	125V DC				250V DC
30	3	10	20	30	3	5	1494H-BA3N	1494H-BN3N	1494H-BF3N	
60	10	20	50	60	5	10	1494H-CA3N	1494H-CN3N	1494H-CF3N	
100	20	40	75	100	—	20	1494H-DA3N	1494H-DN3N	1494H-DF3N	
200	30	60	125	150	—	40	1494H-EA3N	1494H-EN3N	1494H-EF3N	

Fusible Disconnect Switch (240V AC)*

Continuous Current Rating [A]	UL & CSA Application Horsepower										Type 1 Cat. No.	Type 3R Cat. No.	Type 12 Cat. No.		
	1-Phase (60 Hz)		3-Phase (60 Hz)				1-Phase (60 Hz)								
	240V AC		240V AC		480V AC		600V AC		125V DC					250V DC	
	Std.	Max.	Std.	Max.	Std.	Max.	Std.	Max.	Std.	Max.				Std.	Max.
30	1.5	3	3	7.5	—	—	—	—	2	3	5	—	1494H-BA3H2	1494H-BN3H2	1494H-BF3H2
60	3	10	7.5	15	—	—	—	—	5	—	10	—	1494H-CA3H2	1494H-CN3H2	1494H-CF3H2
100	7.5	15	15	30	—	—	—	—	—	—	20	—	1494H-DA3H2	1494H-DN3H2	1494H-DF3H2
200	15	—	25	60	—	—	—	—	—	—	40	—	1494H-EA3H2	1494H-EN3H2	1494H-EF3H2

* Includes a neutral lug for four wire applications.

Fusible Disconnect Switch (600V AC)

Continuous Current Rating [A]	UL & CSA Application Horsepower												Type 1 Cat. No.	Type 3R Cat. No.	Type 12 Cat. No.
	1-Phase (60 Hz)		3-Phase (60 Hz)						1-Phase (60 Hz)		250V DC				
	240V AC		240V AC		480V AC		600V AC		125V DC		250V DC				
	Std.	Max.	Std.	Max.	Std.	Max.	Std.	Max.	Std.	Max.	Std.	Max.			
30	1.5	3	3	7.5	5	15	7.5	20	2	3	5	—	1494H-BA3H6	1494H-BN3H6	1494H-BF3H6
60	3	10	7.5	15	15	30	15	50	5	—	10	—	1494H-CA3H6	1494H-CN3H6	1494H-CF3H6
100	7.5	15	15	30	25	60	30	75	—	—	20	—	1494H-DA3H6	1494H-DN3H6	1494H-DF3H6
200	15	—	25	60	50	125	60	150	—	—	40	—	1494H-EA3H6	1494H-EN3H6	1494H-EF3H6