

Pinout and Color Code

Color Code	Face View Pinout									
	2-Pin		3-Pin		4-Pin		5-Pin		6-Pin	
	Female	Male	Female	Male	Female	Male	Female	Male	Female	Male
A (US)	1 White 2 Black		1 Green 2 Black 3 White		1 Black 2 White 3 Red 4 Green		1 White 2 Red 3 Green 4 Orange 5 Black		1 White 2 Red 3 Green 4 Orange 5 Black 6 Blue	
B (Auto)	—		1 Green 2 Red/Black Tr 3 Red/White Tr		1 Red/Black Tr 3 Red 2 Red/White Tr 4 Green		1 Red/White Tr 2 Red 3 Green 4 Red/Yellow Tr 5 Red/Black Tr		—	
C (IEC)	—		—		1 Black 2 Blue 3 Brown 4 White		1 Black 2 Blue 3 Grey 4 Brown 5 White		—	

Product Selection

Cordsets 

Pin Count	Assembly Rating	Color Code	Cat. No.			
			Straight Female	Right Angle Female	Straight Male	Right Angle Male
2-Pin	300V, 10 A	A	889N-F2AEC-*F	889N-R2AEC-*F	889N-U2AEC-*F	889N-V2AEC-*F
3-Pin		A	889N-F3AEC-*F	889N-R3AEC-*F	889N-U3AEC-*F	889N-V3AEC-*F
4-Pin	300V, 7 A	B	889N-F3AEA-*F	889N-R3AEA-*F	889N-U3AEA-*F	889N-V3AEA-*F
		A	889N-F4AEC-*F	889N-R4AEC-*F	889N-U4AEC-*F	889N-V4AEC-*F
		C	889N-F4AEA-*F	889N-R4AEA-*F	889N-U4AEA-*F	889N-V4AEA-*F
5-Pin	300V, 5.6 A	B	889N-F4AE-*F	889N-R4AE-*F	889N-U4AE-*F	889N-V4AE-*F
		A	889N-F5AEC-*F	889N-R5AEC-*F	889N-U5AEC-*F	889N-V5AEC-*F
		C	889N-F5AEA-*F	889N-R5AEA-*F	889N-U5AEA-*F	889N-V5AEA-*F
6-Pin		A	889N-F5AE-*F	889N-R5AE-*F	889N-U5AE-*F	889N-V5AE-*F
		A	889N-F6AEC-*F	889N-R6AEC-*F	889N-U6AEC-*F	889N-V6AEC-*F

Patchcords 

Pin Count	Assembly Rating	Cat. No.			
		Straight Female Straight Male	Straight Female Right Angle Male	Right Angle Female Straight Male	Right Angle Female Right Angle Male
2-Pin	300V, 10 A	889N-F2AENU-†F	889N-F2AENV-†F	889N-R2AENU-†F	889N-R2AENV-†F
3-Pin		889N-F3AENU-†F	889N-F3AENV-†F	889N-R3AENU-†F	889N-R3AENV-†F
4-Pin	300V, 7 A	889N-F4AENU-†F	889N-F4AENV-†F	889N-R4AENU-†F	889N-R4AENV-†F
5-Pin	300V, 5.6 A	889N-F5AENU-†F	889N-F5AENV-†F	889N-R5AENU-†F	889N-R5AENV-†F
6-Pin		889N-F6AENU-†F	889N-F6AENV-†F	889N-R6AENU-†F	889N-R6AENV-†F

* Replace symbol with 6 (6 ft), 12 (12 ft), or 20 (20 ft) for standard cable lengths.
 † Replace symbol with 3 (3 ft), 6 (6 ft), 12 (12 ft), or 20 (20 ft) for standard cable lengths.

Note: Stainless steel connector versions may be ordered by adding an "S" to the bulletin number, e.g., 889NS-F3AEC-*F.