

# TPI Industrial Assembled Circulator Heads and Mounts

## Features

- Pull chain switch
- SJT type 3 conductor, 12' long cord
- Steel hub/spider aluminum paddle blades
- Coated steel guards
- Meets OSHA standards

DIMENSIONS	
24"	27" Diameter x 14.5" Depth
30"	33.5" Diameter x 14.5" Depth



## Motor Specifications

- 2-Speed
- 1 Phase, 120V
- Ball bearing
- Frame size: 48
- Totally enclosed
- Permanent split capacitor
- Permanently lubricated
- 1/2" Shaft

## Product Specifications

- Oscillating model oscillates in a 90° arc or can be locked in a fixed position
- Metal gears in the oscillating mechanism allow the fan to operate at a maximum 30° downward tilt



## Standard Models


FAN TYPE		HEAVY DUTY			HIGH PERFORMANCE			STANDARD INDUSTRIAL			OSCILLATING		
FAN HEAD	HP	1/2			1/3			1/4			1/4		
	TYPE	STATIONARY			STATIONARY			STATIONARY			OSCILLATING		
CFM / RPM WEIGHT AMPS	24"	8600 / 7100 1100 / 800	44 lbs.	3.5	7000 / 5200 1100 / 800	40 lbs.	2.8	6800 / 5000 1100 / 800	40 lbs.	2.5	6800 / 5000 1100 / 800	44 lbs.	2.5
	30"	9850 / 8100 1100 / 800	48 lbs.	4	8200 / 6200 1100 / 800	44 lbs.	3.0	7900 / 6000 1100 / 800	44 lbs.	2.7	7900 / 6000 1100 / 800	48 lbs.	2.7
WARRANTY		5 YEARS			3 YEARS			1 YEAR			1 YEAR		
SIZE	UPC# 686334	MODEL	LIST	UPC# 686334	MODEL	LIST	UPC# 686334	MODEL	LIST	UPC# 686334	MODEL	LIST	
24"	853927	HDH-24G	551	798983	IHP 24-H	421	796163	ACH 24	329	796361	ACH 24-O	508	
30"	852869	HDH-30G	570	798990	IHP 30-H	440	796170	ACH 30	341	796378	ACH 30-O	526	

Six factory assembled and tested fan mounts that can be used with any of the non-oscillating TPI Industrial heads.

## Industrial Mounts



PEDESTAL



WALL MOUNT



SUSPENSION MOUNT



I-BEAM MOUNT



CEILING MOUNT



POLE MOUNT

ATTACHES TO 4", 6", OR 8" POLES.