

Steel Compression Connectors



Features/Industry Standards

- Strong steel construction
- Stamped steel nut on 1/2"-2"
- Malleable nut on 2-1/2"-4" for better grip*
- Connectors available with and without insulated throats
- UL Standard 514B, UL Listed File # E-172239*
- C-UL Listed for Canada
- Federal Specification A-A-50553A
- ANSI/NEMA FB-1

Specification/Ordering Information

PRODUCT CODE	CATALOG NUMBER	WEIGHT PER/C	TRADE SIZE	DIMENSION IN INCHES			CARTON COUNT	
				A	B	C	INNER	MASTER
0202-24-00	CC-50	13	1/2"	1.614	0.354	1.102	50	500
0203-22-00	CC-75	18	3/4"	1.898	0.535	1.898	25	250
0204-20-00	CC-100	27	1"	2.106	0.421	1.654	20	200
0205-10-00	CC-125	48	1-1/4"	2.677	0.600	1.969	10	100
0206-10-00	CC-150	60	1-1/2"	3.071	0.650	2.244	10	100
0207-05-00	CC-200	82	2"	3.268	0.650	2.717	5	50
0208-08-00	CC-250	152	2-1/2"	3.780	0.748	3.760	*	8
0209-06-00	CC-300	211	3"	4.291	0.827	4.567	*	6
0210-04-00	CC-350	242	3-1/2"	4.449	0.945	5.079	*	4
0211-04-00	CC-400	287	4"	4.803	0.984	5.079	*	4
Insulated Throat								
0212-24-00	CCI-50	13	1/2"	1.614	0.354	1.102	50	500
0213-22-00	CCI-75	18	3/4"	1.898	0.535	1.898	25	250
0214-20-00	CCI-100	27	1"	2.106	0.421	1.654	20	200
0215-10-00	CCI-125	48	1-1/4"	2.677	0.600	1.969	10	100
0216-10-00	CCI-150	60	1-1/2"	3.071	0.650	2.244	10	100
0217-05-00	CCI-200	82	2"	3.268	0.650	2.717	5	50
0218-08-00	CCI-250	152	2-1/2"	3.780	0.748	3.760	*	8
0219-06-00	CCI-300	211	3"	4.291	0.827	4.567	0	6
0220-04-00	CCI-350	242	3-1/2"	4.449	0.945	5.079	*	4
0221-04-00	CCI-400	287	4"	4.803	5.709	0.984	*	4

* UL tri-listing pending for use with EMT, IMC & Rigid Conduit for connectors 2-1/2-4".

1/2" - 4"

