



Made in the USA Since 1946

Strain Relief Cord Connectors Straight

- Industrial specification grade, screw machined steel, zinc plated
- Provides a UL liquid tight and strain relief termination for flexible type, neoprene, vinyl, or PVC control cord and cable
- Color-coded grommet to indicate cable diameter range

SPEC-grade



UL rated suitable for hazardous locations
Class I, Div. 2; Class II, Div. 1 and 2;
Class III, Div. 1 and 2; NEC 501-4(b), 505-4(a), 503-3(a)

Featuring:
EZ-Torque Compression Nut

Straight Connectors - Steel

Cat. #	Color	Size	Cable Ranges		Unit Ctn	Std Pkg	WT/ 100
			Min.	Max			
CG50A250	Red	1/2"	.150	.250	25	250	12
CG50A350	White	1/2"	.250	.350	25	250	12
CG50A450	Blue	1/2"	.350	.460	25	250	12
CG50A560	Green	1/2"	.450	.560	25	250	12
CG50A650	Brown	1/2"	.560	.650	25	250	12
CG75A250	Red	3/4"	.150	.250	10	100	10
CG75A350	White	3/4"	.250	.350	10	100	10
CG75A450	Blue	3/4"	.350	.460	10	100	10
CG75A560	Green	3/4"	.450	.560	10	100	10
CG75A650	Brown	3/4"	.560	.650	10	100	10
CG75B750	Yellow	3/4"	.650	.750	10	100	10
CG75B850	Purple	3/4"	.750	.850	10	100	10
CG100B560	Green	1"	.450	.560	5	50	28
CG100B650	Brown	1"	.560	.650	5	50	28
CG100B750	Yellow	1"	.650	.750	5	50	28
CG100B850	Purple	1"	.750	.850	5	50	28
CG100C950	Grey	1"	.850	.950	5	50	28
CG100C1050	Black	1"	.950	1.050	5	50	28

Cord Connectors 1