



Threaded Rigid and IMC Conduit Hubs

Suitable for use in Class I, Division 2

COMMERCIAL PRODUCTS: RIGID AND IMC FITTINGS

Commercial Products

Catalog Number	Trade Size (Inches)	Hole Diameter in Inches/Millimeters		Panel Thickness in Inches/Millimeters		Dimensions in Inches/Millimeters		Weight Lbs./Kgs. Per 100
		Max.	Min.	Max.	Min.	A	B	
Straight — Malleable Iron								
HUB-125 †	1-1/4	1.69/	1.78/	0.06/	0.08/	1.80/	2.31/	77.00/
		42.9	45.2	1.5	2.0			
HUB-150 †	1-1/2	1.84/	2.03/	0.09/	0.08/	1.83/	2.63/	92.00/
		46.7	51.6	2.3	7.9			
HUB-200 †	2	2.09/	2.53/	0.09/	0.08/	1.88/	3.13/	134.00/
		53.1	64.3	2.3	2.0			
HUB-250 †	2-1/2	2.59/	3.02/	0.09/	0.31/	2.39/	3.63/	236.00/
		65.8	76.7	2.3	7.9			
HUB-300 †	3	2.89/	3.64/	0.09/	0.31/	2.48/	1.00/	310.00/
		73.4	92.5	2.3	7.9			
HUB-350 †	3-1/2	3.52/	4.13/	0.09/	0.31/	3.19/	4.81/	400.00/
		89.4	104.9	2.3	7.9			
HUB-400 †	4	4.02/	4.63/	0.09/	0.31/	2.63/	5.44/	475.00/
		102.1	117.6	2.3	7.9			
90° — Malleable Iron								
HUB-9050	1/2	0.88/	0.94/	0.06/	0.08/	1.28/	0.88/	36.00/
		22.4	23.9	1.5	2.0			
HUB-9075	3/4	0.97/	1.16/	0.09/	0.08/	1.44/	0.94/	50.00/
		24.6	29.5	2.3	6.4			
HUB-90100	1	1.09/	1.41/	0.06/	0.08/	1.63/	1.13/	75.00/
		27.7	35.8	1.5	2.0			
		1.22/	1.47/	0.09/	0.25/	41.4	28.7	34.02
		31.0	37.3	2.3	6.4			



† PVC coating available on select hubs. Add suffix **-PVC** to catalog number.